



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	M4/6.3G
Product ID:	1SNA115279R0200
EAN:	3472591152791
Catalog Description:	M4/6.3G Specific Terminal Blocks Feed-through Grey
Long Description:	M4/6.3G Specific Terminal Blocks - Feed-through - Grey, 4mm ² RatedCrossSection, 6mm Spacing G32, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

Ordering

Minimum Order Quantity:	25 piece
Customs Tariff Number:	85369010
EAN:	3472591152791

Dimensions

Product Net Height:	58 mm
Product Net Depth:	33.5 mm
Product Net Weight:	11 g
Product Net Width:	6 mm

Container Information

Package Level 1 Width:	66 mm
Package Level 1 Length:	150 mm
Package Level 1 Height:	41 mm
Package Level 1 Gross Weight:	0.275 kg
Package Level 1 EAN:	3472591152791
Package Level 2 Units:	900 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 3 Units:	43200 piece
Product Packing Type:	Box
Package Level 1 Units:	25 piece

Technical

Spacing:	6 mm
Connection Type:	Quick-connect - Screw clamp
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22 ... 4 mm ² Screw Clamp / Rigid 1x 0.2 ... 4 mm ²
Rated Current (I _n):	Main Circuit 25 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 480 A
Rated Voltage (U _r):	500 V
Rated Impulse Withstand Voltage (U _{imp}):	6000 V
Pollution Degree:	2
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	4 mm
Tightening Torque:	acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m
Rated Cross-Section:	4 mm ²

Technical UL/CSA

Flammability According to UL94: V2

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q1
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225003C1007
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230021F0201

Classifications

ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
M4/6.3G Specific Terminal Blocks Feed-through Grey	1SNA115279R0200	M4/6.3G	Buy on EAN