



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

### General Information

Extended Product Type:	M6/8.STA
Product ID:	1SNA115359R0200
EAN:	3472591153590
Catalog Description:	M6/8.STA Screw Clamp Terminal Blocks - Test disconnect with a screwdriver sliding link - Grey
Long Description:	M6/8.STA Screw Clamp Terminal Blocks - Disconnect - Grey, 6mm <sup>2</sup> RatedCrossSection, 8mm Spacing G32, TH 35-7.5, TH 35-15 Rail

### Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

### Ordering

Minimum Order Quantity:	25 piece
Customs Tariff Number:	85369010
Color:	Grey

### Dimensions

Product Net Height:	61 mm
Product Net Depth:	49 mm
Product Net Weight:	30 g
Product Net Width:	8 mm

### Technical

Spacing:	8 mm
Connection Type:	Screw clamp
Function:	Disconnect
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 6 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 10 mm <sup>2</sup>
Gauge Type:	A5
Rated Current (I <sub>n</sub> ):	Main Circuit 30 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 480 A
Rated Voltage (U <sub>r</sub> ):	500 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	11.0 mm
Recommended Screw Driver:	5.5 mm
Tightening Torque:	acc. IEC 60947-1 0.8 N·m Manufacturer 1 N·m
Rated Cross-Section:	6 mm <sup>2</sup>

### Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 22 ... 8 AWG
Connecting Capacity UL/CSA:	Screw Clamp / Rigid 22 ... 8 AWG Stranded 8 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

### Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

### Certificates and Declarations (Document Number)

cUL Certificate:	1SND161001A0208
------------------	-----------------


<b>Declaration of Conformity - CE:</b>	1SND225002C1007
<b>EAC Certificate:</b>	1SND161009A1100
<b>RoHS Information:</b>	1SND230023F0208

### Classifications

<b>E-nummer:</b>	2925562
<b>ETIM 4:</b>	EC000902 - (Knife) disconnect terminal block
<b>ETIM 5:</b>	EC000902 - (Knife) disconnect terminal block
<b>Object Classification Code:</b>	X

### Container Information

<b>Package Level 1 Width:</b>	80 mm
<b>Package Level 1 Length:</b>	208 mm
<b>Package Level 1 Height:</b>	60 mm
<b>Package Level 1 Gross Weight:</b>	0.75 kg
<b>Package Level 1 EAN:</b>	3472591153590
<b>Package Level 2 Units:</b>	650 piece
<b>Package Level 2 Width:</b>	300 mm
<b>Package Level 2 Length:</b>	500 mm
<b>Package Level 2 Height:</b>	300 mm
<b>Package Level 2 Gross Weight:</b>	20.000 kg
<b>Package Level 3 Units:</b>	15600 piece
<b>Product Packing Type:</b>	Box
<b>Package Level 1 Units:</b>	25 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
M6/8.STA Screw Clamp Terminal Blocks - Test disconnect with a screwdriver sliding link - Grey	1SNA115359R0200	M6/8.STA	<a href="#">Buy on EAN</a>