



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	M4/6.4A
Product ID:	1SNA115479R2300
EAN:	3472591154795
Catalog Description:	M4/6.4A Screw Clamp Terminal Blocks - Feed-through - Grey
Long Description:	M4/6.4A Screw Clamp Terminal Blocks - Feed-through - Grey, 4mm ² RatedCrossSection, 6mm Spacing G32, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
EAN:	3472591154795

Dimensions

Product Net Height:	63.5 mm
Product Net Depth:	40.5 mm
Product Net Weight:	20 g
Product Net Width:	6 mm

Container Information

Package Level 1 Width:	126 mm
Package Level 1 Length:	155 mm
Package Level 1 Height:	64 mm
Package Level 1 Gross Weight:	1 kg
Package Level 1 EAN:	3472591154795
Package Level 2 Units:	500 piece
Package Level 3 Units:	24000 piece
Product Packing Type:	Box
Package Level 1 Units:	50 piece

Technical

Spacing:	6 mm
Connection Type:	Screw clamp
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22 ... 4 mm ² Screw Clamp / Rigid 1x 0.2 ... 4 mm ² Screw Clamp / With Insulated Ferrule 1x 2.5 mm ²
Gauge Type:	A4
Rated Current (I _n):	Main Circuit 32 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 480 A
Rated Voltage (U _r):	800 V
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Dielectric Test Voltage:	2500 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	4 mm
Tightening Torque:	acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m
Rated Cross-Section:	4 mm ²

Technical UL/CSA

**Connecting Capacity Main Circuit
UL/CSA:** Screw Clamp / Rigid 1x 22 ... 10 AWG

Connecting Capacity UL/CSA: Screw Clamp / Rigid 22 ... 10 AWG
Stranded 10 AWG

Flammability According to UL94: V0

**Maximum Operating Voltage
UL/CSA:** Main Circuit 600 V

Environmental

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C
Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SND225001C1009

EAC Certificate: 1SND161009A1100

RoHS Information: 1SND230023F0208

Classifications

ETIM 4: EC000897 - Feed-through terminal block

ETIM 5: EC000897 - Feed-through terminal block

Object Classification Code: X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
M4/6.4A Screw Clamp Terminal Blocks - Feed-through - Grey	1SNA115479R2300	M4/6.4A	Buy on EAN