



Automatzación Eléctrica
Especialistas en Automatzación

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	M4/8.SF.NC
Product ID:	1SNA140033R2400
EAN:	3472591400335
Catalog Description:	M4/8.SF.NC Screw Clamp Terminal Blocks - Corrosive Environments - Fuse Grey
Long Description:	M4/8.SF.NC Screw Clamp Terminal Blocks for corrosive environments - Fuse

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
EAN:	3472591400335

Dimensions

Product Net Height:	56.5 mm
Product Net Depth:	41 mm
Product Net Weight:	14 g
Product Net Width:	8 mm

Container Information

Package Level 1 Width:	101 mm
Package Level 1 Length:	265 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.7 kg
Package Level 1 EAN:	3472591400335
Package Level 2 Units:	450 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 2 Gross Weight:	6.2 kg
Package Level 3 Units:	21600 piece
Product Packing Type:	Box
Package Level 1 Units:	50 piece

Technical

Spacing:	8 mm
Connection Type:	Screw clamp
Function:	Fuse
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 4 mm ² Screw Clamp / Rigid 1x 0.5 ... 6 mm ²
Gauge Type:	A4
Rated Current (I _n):	Main Circuit 6.3 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 480 A
Rated Voltage (U _r):	630 V
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Pollution Degree:	2
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	4 mm
Tightening Torque:	acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m
Rated Cross-Section:	4 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 22 ... 12 AWG
Connecting Capacity UL/CSA:	Stranded 12 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225029C1006
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230023F0208

Classifications

ETIM 4:	EC000899 - Fuse terminal block
ETIM 5:	EC000899 - Fuse terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
M4/8.SF.NC Screw Clamp Terminal Blocks - Corrosive Environments - Fuse Grey	1SNA140033R2400	M4/8.SF.NC	Buy on EAN