



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## M35/16.P



Extended Product Type:	M35/16.P		
Product ID:			
EAN:	1SNA165111R1400		
Catalog Description:	3472591651119 M35/16 P. Scrow Clamp Torminal Blocks - Cround - Groon Vallow		
• •	M35/16.P Screw Clamp Terminal Blocks - Ground - Green-Yellow		
Long Description:	M35/16.P Screw Clamp Terminal Blocks - Ground - Green-Yellow,35mm <sup>2</sup> RatedCrossSection, 16mm Spacing G32, TH 35-7.5, TH 35-15 Rail		
Categories			
	nd Systems » Connection Devices » Terminal Blocks » SNA Series		
Ordering			
Minimum Order Quantity:	20 piece		
Customs Tariff Number:	85369010		
EAN:	3472591651119		
Dimensions			
Product Net Height:	49 mm		
Product Net Depth:	46.5 mm		
Product Net Weight:	50.5 g		
Product Net Width:	16 mm		
Container Information			
Package Level 1 Width:	81 mm		
Package Level 1 Length:	200 mm		
Package Level 1 Height:	53 mm		
Package Level 1 Gross Weight:	1.01 kg		
Package Level 1 EAN:	3472591651119		
Package Level 2 Units:	300 piece		
Package Level 2 Width:	300 piece		
Package Level 2 Length:	500 mm		
Package Level 2 Height:	150 mm		
Package Level 2 Gross Weight:	15.350 kg		
Package Level 3 Units:	14400 piece		
Product Packing Type:	Box		
Package Level 1 Units:	20 piece		
Technical			
Spacing:	16 mm		
Connection Type:	Screw clamp		
Function:	Ground		
Number of Levels:	1		
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 4 35 mm <sup>2</sup>		
connecting capacity-main circuit.	Screw Clamp / Rigid 1x 4 50 mm <sup>2</sup>		
	Screw Clamp / With Insulated Ferrule 1x 35 mm <sup>2</sup>		
Gauge Type:	B9		
Rated Short-time Withstand Curren	tt for 1 s 4200 A		
(I <sub>cw</sub> ):			
Dielectric Test Voltage:	3500 V		
Pollution Degree:	3		
Insulation Material:	Polyamide		
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715		
	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715		
Wire Stripping Length	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715		
Wire Stripping Length: Recommended Screw Driver:	17.0 mm		
Recommended Screw Driver:	8 mm		
Timbéo miner Tourness	acc. IEC 60947-1 2.8 N·m Manufacturer 3 N·m		
Tightening Torque:			
Tightening Torque: Rated Cross-Section:	35 mm <sup>2</sup>		
Rated Cross-Section:			

Connecting Capacity UL/CSA:	Screw Clamp / Rigid 8 0 AWG Stranded 0 AWG
Flammability According to UL94:	V0
Environmental	
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 +110 °C Storage -55 +110 °C

## **Certificates and Declarations (Document Number)**

CSA Certificate:	1SND161039A0201
cUL Certificate:	1SND161011A0202
Declaration of Conformity - CE:	1SND225004C1008
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230023F0208

## Classifications

E-nummer:	2925529
ETIM 4:	EC000901 - Ground terminal block
ETIM 5:	EC000901 - Ground terminal block
Object Classification Code:	X







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
M35/16.P Screw Clamp Terminal Blocks - Ground - Green-Yellow	1SNA165111R1400	M35/16.P	Buy on EAN