



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE



### **General Information**

Extended Product Type: M10/10.P

 Product ID:
 1SNA165115R1000

 EAN:
 3472591651157

Catalog Description: M10/10.P Screw Clamp Terminal Blocks - Ground - Green-Yellow

Long Description: M10/10.P Screw Clamp Terminal Blocks - Ground - Green-Yellow,10mm<sup>2</sup>

RatedCrossSection, 10mm Spacing G32, TH 35-7.5, TH 35-15 Rail

# **Categories**

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

#### Ordering

Minimum Order Quantity:50 pieceCustoms Tariff Number:85369010Color:Green-Yellow

#### **Dimensions**

Product Net Height:43.5 mmProduct Net Depth:40.5 mmProduct Net Weight:29 gProduct Net Width:10 mm

### **Technical**

Spacing:10 mmConnection Type:Screw clampFunction:Ground

Number of Levels: 1

Connecting Capacity-Main Circuit: Screw Clamp / Flexible 1x 0.5 ... 10 mm² Screw Clamp / Rigid 1x 0.5 ... 16 mm²

Screw Clamp / With Insulated Formula 1x 6 mg

Screw Clamp / With Insulated Ferrrule 1x 6 mm<sup>2</sup>

Gauge Type: B6

Rated Short-time Withstand Current for 1 s 1200 A

(I<sub>cw</sub>):

Pollution Degree: 3

Insulation Material: Polyamide

**Mounting on DIN Rail:** G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715

TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

Wire Stripping Length: 12.0 mm

Recommended Screw Driver: 5.5 ... 6 mm

**Tightening Torque:** acc. IEC 60947-1 1.2 N·m

Manufacturer 1.4 N·m

Rated Cross-Section: 10 mm<sup>2</sup>

# Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:

Screw Clamp / Rigid 1x 20 ... 6 AWG

Connecting Capacity UL/CSA:

Screw Clamp / Rigid 20 ... 6 AWG

Stranded 6 AWG

Flammability According to UL94: V0

### **Environmental**

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C Storage -55 ... +110 °C

## **Certificates and Declarations (Document Number)**

CSA Certificate:	1SND161039A0201
cUL Certificate:	1SND161011A0202
Declaration of Conformity - CE:	1SND225004C1008
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230023F0208

### Classifications

E-nummer: 2925527

ETIM 4: EC000901 - Ground terminal block

ETIM 5: EC000901 - Ground terminal block

Object Classification Code: X

### **Container Information**

Package Level 1 Width: 101 mm Package Level 1 Length: 220 mm Package Level 1 Height: 47 mm Package Level 1 Gross Weight: 1.45 kg 3472591651157 Package Level 1 EAN: 500 piece Package Level 2 Units: Package Level 2 Width: 300 mm Package Level 2 Length: 500 mm Package Level 2 Height: 150 mm Package Level 2 Gross Weight: 14.850 kg Package Level 3 Units: 24000 piece **Product Packing Type:** Box Package Level 1 Units: 50 piece







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
M10/10.P Screw Clamp Terminal Blocks - Ground - Green-Yellow	1SNA165115R1000	M10/10.P	Buy on EAN