



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## M6/13.FF



## **General Information** M6/13.FF Extended Product Type: Product ID: 1SNA195626R1700 EAN: 3472591956269 **Catalog Description:** M6/13.FF Ring lug terminal blocks Feed-through Beige Long Description: M6/13.FF Specific Terminal Blockss - Feed-through - Beige,6mm<sup>2</sup> RatedCrossSection, 13mm Spacing G32, TH 35-7.5, TH 35-15 Rail Categories Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Railway Terminal Blocks Ordering Minimum Order Quantity: 25 piece **Customs Tariff Number:** 85369010 Color: Beige Dimensions 51.5 mm **Product Net Height:** Product Net Depth: 33 mm **Product Net Weight:** 16 q **Product Net Width:** 13 mm Technical Spacing: 13 mm Stud Connection Type: Function: Feed-through Number of Levels: 1 **Connecting Capacity-Main Circuit:** Stud / Flexible 1x 0.5 ... 6 mm<sup>2</sup> Stud / Rigid 1x 0.5 ... 6 mm<sup>2</sup> Rated Current (In): Main Circuit 41 A Rated Short-time Withstand Current for 1 s 8000 A (I<sub>cw</sub>): 800 V Rated Voltage (Ur): **Rated Impulse Withstand Voltage** 8 kV (U<sub>imp</sub>): **Insulation Material:** Polyamide Mounting on DIN Rail: G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 **Tightening Torque:** Cable Lug 2.5 N·m **Rated Cross-Section:** 6 mm<sup>2</sup> **Technical UL/CSA** Stud / Rigid 1x 20 ... 10 AWG **Connecting Capacity Main Circuit** UL/CSA: Flammability According to UL94: V0 Maximum Operating Voltage Main Circuit 600 V UL/CSA: Environmental **RoHS Status:** Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q2 Operation -55 ... +110 °C Storage -55 ... +110 °C Ambient Air Temperature: **Certificates and Declarations (Document Number)** CSA Certificate: 1SND168003A0200 cUL Certificate: 1SND168000A0202 **Declaration of Conformity - CE:** 1SND225026C1006 EAC Certificate: 1SND161009A1100 **RoHS** Information: 1SND230021F0201 Classifications

ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
<b>Object Classification Code:</b>	X
Container Information	

Package Level 1 Width:	81 mm
Package Level 1 Length:	220 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.4 kg
Package Level 1 EAN:	3472591956269
Package Level 2 Units:	400 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 3 Units:	28800 piece
Product Packing Type:	Box
Package Level 1 Units:	25 piece







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
M6/13.FF Ring lug terminal blocks Feed-through Beige	1SNA195626R1700		Buy on EAN