



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	ML10/13.SFD
Product ID:	1SNA199166R2600
EAN:	3472591991666
Catalog Description:	ML10/13.SFD Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - with blown fuse indicator by Neon 480V - Black
Long Description:	ML10/13.SFD Screw Clamp Terminal Blocks Fuse

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

Ordering

Minimum Order Quantity:	20 piece
Customs Tariff Number:	85361050
EAN:	3472591991666

Dimensions

Product Net Height:	85 mm
Product Net Depth:	58 mm
Product Net Weight:	54 g
Product Net Width:	13 mm

Container Information

Package Level 1 Width:	172 mm
Package Level 1 Length:	155 mm
Package Level 1 Height:	71 mm
Package Level 1 Gross Weight:	1.08 kg
Package Level 1 EAN:	3472591991666
Package Level 2 Units:	200 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	300 mm
Package Level 2 Gross Weight:	11.300 kg
Package Level 3 Units:	4800 piece
Product Packing Type:	Box
Package Level 1 Units:	20 piece

Technical

Spacing:	13 mm
Connection Type:	Screw clamp
Function:	Fuse
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 10 mm ² Screw Clamp / Rigid 1x 0.5 ... 16 mm ²
Gauge Type:	A6
Rated Current (I _n):	Main Circuit 10 A
Rated Voltage (U _r):	800 V
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Pollution Degree:	3
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	12.0 mm
Recommended Screw Driver:	5.5 mm
Tightening Torque:	acc. IEC 60947-1 1.2 N·m Manufacturer 1.4 N·m
Rated Cross-Section:	10 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 22 ... 10 AWG
---	--------------------------------------

Connecting Capacity UL/CSA:	Screw Clamp / Rigid 22 ... 10 AWG Stranded 10 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

Certificates and Declarations (Document Number)

CSA Certificate:	1SND161066A0201
cUL Certificate:	1SND161000A0203
Declaration of Conformity - CE:	1SND225007C1007
EAC Certificate:	1SND161009A1100
RoHS Information:	1SND230023F0208

Classifications

ETIM 4:	EC000899 - Fuse terminal block
ETIM 5:	EC000899 - Fuse terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
ML10/13.SFD Screw Clamp Terminal Blocks - For 6.3 x 25 and 6.3 x 32 fuses - with blown fuse indicator by Neon 480V - Black	1SNA199166R2600	ML10/13.SFD	Buy on EAN