



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	M4/6.D2.S1R.T
Product ID:	1SNA199456R2100
EAN:	3472591994568
Catalog Description:	M4/6.D2.S1R.T Screw Clamp Terminal Blocks - Disconnect with pull lever - change over type with 3 test sockets - Grey, Black
Long Description:	M4/6.D2.S1R.T Screw Clamp Terminal Blocks - Disconnect - Grey, Black, 4mm ² RatedCrossSection, 6mm Spacing G32, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

Ordering

Minimum Order Quantity:	25 piece
Customs Tariff Number:	85369010
Color:	Grey, Black

Dimensions

Product Net Height:	94.5 mm
Product Net Depth:	92 mm
Product Net Weight:	30 g
Product Net Width:	6 mm

Technical

Spacing:	6 mm
Connection Type:	Screw clamp
Function:	Disconnect
Number of Levels:	2
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.2 ... 4 mm ² Screw Clamp / Rigid 1x 0.2 ... 4 mm ²
Gauge Type:	A4
Rated Current (I _n):	Main Circuit 10 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 120 A
Rated Voltage (U _r):	500 V
Rated Impulse Withstand Voltage (U _{imp}):	6000 V
Dielectric Test Voltage:	2500 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	4 mm
Tightening Torque:	acc. IEC 60947-1 0.5 N·m Manufacturer 0.6 N·m
Rated Cross-Section:	4 mm ²

Technical UL/CSA

Connecting Capacity UL/CSA:	Screw Clamp / Rigid 24 ... 10 AWG Stranded 10 AWG
Flammability According to UL94:	V0

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SND225023C1005
EAC Certificate:	1SND161009A1100

RoHS Information: 1SND230023F0208

Classifications

ETIM 4:	EC000902 - (Knife) disconnect terminal block
ETIM 5:	EC000902 - (Knife) disconnect terminal block
Object Classification Code:	X

Container Information

Package Level 1 Width:	147 mm
Package Level 1 Length:	117 mm
Package Level 1 Height:	97 mm
Package Level 1 Gross Weight:	0.75 kg
Package Level 1 EAN:	3472591994568
Package Level 2 Units:	375 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	300 mm
Package Level 2 Gross Weight:	11.75 kg
Package Level 3 Units:	9000 piece
Product Packing Type:	Box
Package Level 1 Units:	25 piece

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
M4/6.D2.S1R.T Screw Clamp Terminal Blocks - Disconnect with pull lever - change over type with 3 test sockets - Grey. Black	1SNA199456R2100	M4/6.D2.S1R.T	Buy on EAN