



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	D2.5/5.4L
Product ID:	1SNA290016R2200
EAN:	3472592900162
Catalog Description:	D2.5/5.4L Spring Terminal Blocks - Feed-through with 4 connections - Black
Long Description:	D2.5/5.4L Spring Terminal Blocks - Feed-through - Black, 2.5mm <sup>2</sup> RatedCrossSection, 5mm Spacing TH 35-7.5, TH 35-15 Rail

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

## Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
Replacement Product ID (NEW):	<a href="#">1SNK705080R0000</a>
Color:	Black

## Dimensions

Product Net Height:	36.7 mm
Product Net Length:	36.7 mm
Product Net Depth:	36.7 mm
Product Net Weight:	8 g
Product Net Width:	5 mm

## Technical

Spacing:	5 mm
Connection Type:	Spring
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Spring Clamp / Flexible 1x 0.12 ... 2.5 mm <sup>2</sup> Spring Clamp / Rigid 1x 0.12 ... 4 mm <sup>2</sup> Spring Clamp / With Insulated Ferrule 1x 0.5 ... 1.5 mm <sup>2</sup>
Gauge Type:	A2
Rated Current (I <sub>n</sub> ):	Main Circuit 24 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 300 A
Rated Voltage (U <sub>r</sub> ):	800 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8000 V
Dielectric Test Voltage:	3000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	3.5 mm
Rated Cross-Section:	2.5 mm <sup>2</sup>

## Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Spring Clamp / Flexible 1x 26 ... 12 AWG Spring Clamp / Rigid 1x 26 ... 12 AWG
Connecting Capacity UL/CSA:	Stranded 12 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

## Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q4
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

## Certificates and Declarations (Document Number)

cUL Certificate:	1SND162000A0204
Declaration of Conformity - CE:	1SND225016C1007
EAC Certificate:	1SND162001A1100
RoHS Information:	1SND230488F0201

## Classifications

ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X

## Container Information

Package Level 1 Width:	165 mm
Package Level 1 Length:	130 mm
Package Level 1 Height:	43 mm
Package Level 1 Gross Weight:	0.4 kg
Package Level 1 EAN:	3472592900162
Package Level 2 Units:	1250 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	300 mm
Package Level 2 Gross Weight:	10.500 kg
Package Level 3 Units:	30000 piece
Product Packing Type:	Box
Package Level 1 Units:	50 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
D2.5/5.4L Spring Terminal Blocks - Feed-through with 4 connections - Black	1SNA290016R2200	D2.5/5.4LNG	<a href="#">Buy on EAN</a>