



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE



## **General Information**

Extended Product Type:D2.5/5.P.2LProduct ID:1SNA290029R0700

**EAN:** 3472592900292

Catalog Description: D2.5/5.P.2L Spring Terminal Blocks - Ground with 2 connections - Green-Yellow

Long Description: D2.5/5.P.2L Spring Terminal Blocks - Ground - Green-Yellow, 2.5mm² RatedCrossSection,

5mm Spacing TH 35-7.5, TH 35-15 Rail

# Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

#### Ordering

Minimum Order Quantity:50 pieceCustoms Tariff Number:85369010

Replacement Product ID (NEW): 1SNK705150R0000

Color: Green-Yellow

## **Dimensions**

Product Net Height:58 mmProduct Net Depth:30.5 mmProduct Net Weight:9 gProduct Net Width:5 mm

#### **Technical**

Spacing:5 mmConnection Type:SpringFunction:GroundNumber of Levels:1

Connecting Capacity-Main Circuit: Spring Clamp / Flexible 1x 0.12 ... 2.5 mm²

Spring Clamp / Rigid 1x 0.12 ... 4 mm<sup>2</sup>

Spring Clamp / With Insulated Ferrrule 1x 0.5 ... 1.5 mm<sup>2</sup>

Gauge Type: A2

Rated Current (I<sub>n</sub>): Main Circuit 300 A

Rated Short-time Withstand Current for 1 s 300  $\mbox{A}$ 

(I<sub>cw</sub>):

Pollution Degree: 3

**Degree of Protection:** acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

Insulation Material: Polyamide

Mounting on DIN Rail: TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

Wire Stripping Length: 9.5 mm

Recommended Screw Driver: 3.5 mm

Rated Cross-Section: 2.5 mm<sup>2</sup>

## Technical UL/CSA

Connecting Capacity Main Circuit Spring Clamp / Flexible 1x 26 ... 12 AWG UL/CSA: Spring Clamp / Rigid 1x 26 ... 12 AWG

Connecting Capacity UL/CSA: Stranded 12 AWG

Flammability According to UL94: V0

# **Environmental**

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C

Storage -55 ... +110 °C

# **Certificates and Declarations (Document Number)**

 cUL Certificate:
 1SND162000A0204

 Declaration of Conformity - CE:
 1SND225017C1006

 EAC Certificate:
 1SND162001A1100

 RoHS Information:
 1SND230488F0201

## Classifications

ETIM 4: EC000901 - Ground terminal block
ETIM 5: EC000901 - Ground terminal block

Object Classification Code: X

# **Container Information**

Package Level 1 Width: 81 mm Package Level 1 Length: 220 mm 47 mm Package Level 1 Height: Package Level 1 Gross Weight: 0.45 kg Package Level 1 EAN: 3472592900292 Package Level 2 Units: 750 piece Package Level 2 Width: 300 mm 500 mm Package Level 2 Length: Package Level 2 Height: 150 mm Package Level 2 Gross Weight: 7.100 kg Package Level 3 Units: 36000 piece **Product Packing Type:** Box Package Level 1 Units: 50 piece







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
D2.5/5.P.2L Spring Terminal Blocks - Ground with 2 connections - Green-Yellow	1SNA290029R0700	D2.5/5.P.2L	Buy on EAN