



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	D2.5/8.SFLT.2L
Product ID:	1SNA290093R2000
EAN:	3472592900933
Catalog Description:	D2.5/8.SFLT.2L Spring Terminal Blocks - For 5 x 20 and 5 x 25 fuses - with blown fuse indicator and test sockets - Grey
Long Description:	D2.5/8.SFLT.2L Spring Terminal Blocks - Fuse - Grey, 2.5mm ² RatedCrossSection, 8mm Spacing TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
Replacement Product ID (NEW):	1SNK706412R0000
Color:	Grey

Dimensions

Product Net Height:	80 mm
Product Net Depth:	45.5 mm
Product Net Weight:	15 g
Product Net Width:	8 mm

Technical

Spacing:	8 mm
Connection Type:	Spring
Function:	Fuse
Number of Levels:	1
Connecting Capacity-Main Circuit:	Spring Clamp / Flexible 1x 0.12 ... 2.5 mm ² Spring Clamp / Rigid 1x 0.12 ... 4 mm ² Spring Clamp / With Insulated Ferrule 1x 0.5 ... 1.5 mm ²
Gauge Type:	A2
Rated Current (I _n):	Main Circuit 6.3 A
Rated Voltage (U _r):	630 V
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	3.5 mm
Rated Cross-Section:	2.5 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Spring Clamp / Flexible 1x 26 ... 12 AWG Spring Clamp / Rigid 1x 26 ... 12 AWG
Connecting Capacity UL/CSA:	Stranded 12 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q4
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

cUL Certificate:	1SND162000A0204
Declaration of Conformity - CE:	1SND225020C1005
EAC Certificate:	1SND162001A1100

RoHS Information: 1SND230488F0201

Classifications

ETIM 4: EC000899 - Fuse terminal block

ETIM 5: EC000899 - Fuse terminal block

Object Classification Code: X

Container Information

Package Level 1 Width: 176 mm

Package Level 1 Length: 200 mm

Package Level 1 Height: 75 mm

Package Level 1 Gross Weight: 0.75 kg

Package Level 1 EAN: 3472592900933

Package Level 2 Units: 450 piece

Package Level 2 Width: 300 mm

Package Level 2 Length: 500 mm

Package Level 2 Height: 300 mm

Package Level 2 Gross Weight: 7.250 kg

Product Packing Type: Box

Package Level 1 Units: 50 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
D2.5/8.SFLT.2L Spring Terminal Blocks - For 5 x 20 and 5 x 25 fuses - with blown fuse indicator and test sockets - Grey	1SNA290093R2000	D2.5/8.SFLT.2L	Buy on EAN