



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|--|
| Extended Product Type: | DH2.5/10.4L |
| Product ID: | 1SNA290271R1600 |
| EAN: | 3472592902715 |
| Catalog Description: | DH2.5/10.4L Spring Terminal Blocks - Miniblocks - Grey |
| Long Description: | DH2.5/10.4L Spring Terminal Blocks Miniblocks |

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

Ordering

| | |
|-------------------------|---------------|
| Minimum Order Quantity: | 100 piece |
| Customs Tariff Number: | 85369010 |
| EAN: | 3472592902715 |

Dimensions

| | |
|---------------------|---------|
| Product Net Height: | 33 mm |
| Product Net Depth: | 24.5 mm |
| Product Net Weight: | 6 g |
| Product Net Width: | 10 mm |

Container Information

| | |
|-------------------------------|---------------|
| Package Level 1 Width: | 135 mm |
| Package Level 1 Length: | 175 mm |
| Package Level 1 Height: | 74 mm |
| Package Level 1 Gross Weight: | 0.6 kg |
| Package Level 1 EAN: | 3472592902715 |
| Package Level 2 Units: | 1600 piece |
| Package Level 2 Width: | 300 mm |
| Package Level 2 Length: | 500 mm |
| Package Level 2 Height: | 300 mm |
| Package Level 2 Gross Weight: | 10.1 kg |
| Package Level 3 Units: | 38400 piece |
| Product Packing Type: | Box |
| Package Level 1 Units: | 100 piece |

Technical

| | |
|--|---|
| Spacing: | 10 mm |
| Connection Type: | Spring |
| Function: | Feed-through |
| Number of Levels: | 1 |
| Connecting Capacity-Main Circuit: | Spring Clamp / Flexible 1x 0.12 ... 2.5 mm ² Spring Clamp / Rigid 1x 0.12 ... 4 mm ² Spring Clamp / With Insulated Ferrule 1x 0.5 ... 1.5 mm ² |
| Gauge Type: | A2 |
| Rated Current (I _n): | Main Circuit 24 A |
| Rated Short-time Withstand Current (I _{cw}): | for 1 s 300 A |
| Rated Voltage (U _r): | 800 V |
| Rated Impulse Withstand Voltage (U _{imp}): | 8000 V |
| Pollution Degree: | 3 |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material: | Polyamide |
| Wire Stripping Length: | 9.5 mm |
| Recommended Screw Driver: | 3.5 mm |
| Rated Cross-Section: | 2.5 mm ² |

Technical UL/CSA

| | |
|--|---------------------------------------|
| Connecting Capacity Main Circuit UL/CSA: | Spring Clamp / Rigid 1x 26 ... 12 AWG |
| Connecting Capacity UL/CSA: | Stranded 12 AWG |

Flammability According to UL94: V0

Maximum Operating Voltage
UL/CSA: Main Circuit 600 V

Environmental

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C
Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

cUL Certificate: 1SND162000A0204

Declaration of Conformity - CE: 1SND225016C1007

EAC Certificate: 1SND162001A1100

RoHS Information: 1SND230488F0201

Classifications

ETIM 4: EC000897 - Feed-through terminal block

ETIM 5: EC000897 - Feed-through terminal block

Object Classification Code: X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|--|-----------------|------------------|----------------------------|
| DH2.5/10.4L Spring Terminal Blocks - Miniblocks - Grey | 1SNA290271R1600 | DH2.5/10.4L | Buy on EAN |