



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	D10/10.2L
Product ID:	1SNA290291R0300
EAN:	3472592902913
Catalog Description:	D10/10.2L Spring Terminal Blocks - Feed-through with 2 connections - Grey
Long Description:	D10/10.2L Spring Terminal Blocks - Feed-through - Grey, 10mm ² RatedCrossSection, 10mm Spacing TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » Solution Series

Ordering

Minimum Order Quantity:	25 piece
Customs Tariff Number:	85369010
Color:	Grey

Dimensions

Product Net Height:	77.5 mm
Product Net Depth:	35.2 mm
Product Net Weight:	24 g
Product Net Width:	10 mm

Technical

Spacing:	10 mm
Connection Type:	Spring
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Spring Clamp / Flexible 1x 0.5 ... 10 mm ² Spring Clamp / Rigid 1x 0.5 ... 16 mm ² Spring Clamp / With Insulated Ferrule 1x 0.5 ... 10 mm ²
Gauge Type:	B6
Rated Current (I _n):	Main Circuit 57 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 1200 A
Rated Voltage (U _r):	1000 V
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	12.0 mm
Recommended Screw Driver:	5.5 mm
Rated Cross-Section:	10 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Spring Clamp / Rigid 1x 20 ... 6 AWG
Connecting Capacity UL/CSA:	Stranded 6 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

cUL Certificate:	1SND162000A0204
Declaration of Conformity - CE:	1SND225016C1007

EAC Certificate:	1SND162001A1100
RoHS Information:	1SND230488F0201

Classifications

ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X

Container Information

Package Level 1 Width:	80 mm
Package Level 1 Length:	250 mm
Package Level 1 Height:	48 mm
Package Level 1 Gross Weight:	0.6 kg
Package Level 1 EAN:	3472592902913
Package Level 2 Units:	350 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 2 Gross Weight:	8.75 kg
Package Level 3 Units:	16800 piece
Product Packing Type:	Box
Package Level 1 Units:	25 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
D10/10.2L Spring Terminal Blocks - Feed-through with 2 connections - Grey	1SNA290291R0300	D10/10.2L	Buy on EAN