



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	D95/26.N
Product ID:	1SNA400371R1100
EAN:	3472594003717
Catalog Description:	D95/26.N Screw Clamp Terminal Blocks - Feed-through - Blue
Long Description:	D95/26.N Screw Clamp Terminal Blocks - Feed-through - Blue, 95mm <sup>2</sup> RatedCrossSection, 26mm Spacing TH 35-7.5, TH 35-15 Rail

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

## Ordering

Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369010
Color:	Blue

## Dimensions

Product Net Height:	87 mm
Product Net Depth:	72 mm
Product Net Weight:	215 g
Product Net Width:	26 mm

## Technical

Spacing:	26 mm
Connection Type:	Screw clamp
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 35 ... 95 mm <sup>2</sup> Screw Clamp / Rigid 1x 35 ... 120 mm <sup>2</sup> Screw Clamp / With Insulated Ferrule 1x 50 mm <sup>2</sup>
Gauge Type:	B12
Rated Current (I <sub>n</sub> ):	Main Circuit 232 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 11400 A
Rated Voltage (U <sub>r</sub> ):	1000 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	26.0 mm
Recommended Screw Driver:	6 mm
Tightening Torque:	acc. IEC 60947-1 9 N·m Manufacturer 9.5 N·m
Rated Cross-Section:	95 mm <sup>2</sup>

## Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 2 ... 0000 AWG
Connecting Capacity UL/CSA:	Screw Clamp / Rigid 2 ... 0000 AWG Stranded 0 AWG
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

## Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
--------------------------	--

## Certificates and Declarations (Document Number)

CSA Certificate:	1SND161051A0202
cUL Certificate:	1SND161009A0202

EAC Certificate:

1SND161009A1100

---

### Classifications

ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X

---

### Container Information

Package Level 1 Width:	135 mm
Package Level 1 Length:	177 mm
Package Level 1 Height:	87 mm
Package Level 1 Gross Weight:	2.15 kg
Package Level 1 EAN:	3472594003717
Package Level 2 Units:	30 piece
Package Level 2 Width:	200 mm
Package Level 2 Length:	300 mm
Package Level 2 Height:	200 mm
Package Level 3 Units:	2880 piece
Product Packing Type:	Box
Package Level 1 Units:	10 piece

---



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
D95/26.N Screw Clamp Terminal Blocks - Feed-through - Blue	1SNA400371R1100	D95/26.N	<a href="#">Buy on EAN</a>