



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	D70/22.P
Product ID:	1SNA400772R1300
EAN:	3472594007722
Catalog Description:	D70/22.P Screw Clamp Terminal Blocks - Ground - Green-Yellow
Long Description:	D70/22.P Screw Clamp Terminal Blocks - Ground - Green-Yellow,70mm ² RatedCrossSection, 22mm Spacing TH 35 ... 15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNA Series

Ordering

Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369010
Color:	Green-Yellow

Dimensions

Product Net Height:	74 mm
Product Net Depth:	68.8 mm
Product Net Weight:	222 g
Product Net Width:	22 mm

Technical

Spacing:	22 mm
Connection Type:	Screw clamp
Function:	Ground
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 16 ... 70 mm ² Screw Clamp / Rigid 1x 16 ... 95 mm ² Screw Clamp / With Insulated Ferrule 1x 50 mm ²
Gauge Type:	B11
Rated Short-time Withstand Current (I _{cw}):	for 1 s 8400 A
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Dielectric Test Voltage:	2200 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	25.0 mm
Recommended Screw Driver:	6 mm
Tightening Torque:	acc. IEC 60947-1 6 N·m Manufacturer 7 N·m
Rated Cross-Section:	70 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 4 ... 00 AWG Screw Clamp / Rigid 1x 4 ... 00 AWG Screw Clamp / With Insulated Ferrule 1x 2 ... 0 AWG
Connecting Capacity UL/CSA:	Screw Clamp / Rigid 4 ... 00 AWG Stranded 0 AWG
Flammability According to UL94:	V0

Environmental

Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

CSA Certificate:	1SND161051A0202
cUL Certificate:	1SND161001A0208

Declaration of Conformity - CE: 1SND225001C1009
EAC Certificate: 1SND161009A1100

Classifications

ETIM 4: EC000901 - Ground terminal block
ETIM 5: EC000901 - Ground terminal block
Object Classification Code: X

Container Information

Package Level 1 Width: 135 mm
Package Level 1 Length: 175 mm
Package Level 1 Height: 74 mm
Package Level 1 Gross Weight: 2.22 kg
Package Level 1 EAN: 3472594007722
Package Level 2 Units: 80 piece
Package Level 2 Width: 300 mm
Package Level 2 Length: 500 mm
Package Level 2 Height: 150 mm
Package Level 3 Units: 3840 piece
Product Packing Type: Box
Package Level 1 Units: 10 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
D70/22.P Screw Clamp Terminal Blocks - Ground - Green-Yellow	1SNA400772R1300	D70/22.P	Buy on EAN