



## Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

## MC812PA U1 (x100) Horizontal



Extended Product Type:	MC812PA U1 (x100) Horizontal			
Product ID:	1SNK168101R0000			
EAN:	3472591681017			
Catalog Description:	MC812PA Terminal Block Markers pre-printed : U1 (x100) Horizontal MC812PA Terminal Block Markers pre-printed : U1 (x100) Horizontal			
Long Description:				
Categories				
	and Systems » Connection Devices » Markers and Marking Systems » Terminal Block			
Markers	,			
Ordering				
Minimum Order Quantity:	1 piece			
Customs Tariff Number:	39269097			
Color:	White			
Dimensions				
Product Net Height:	12 mm			
Product Net Length:	7.6 mm			
Product Net Depth:	7.6 mm			
Product Net Weight:	14 g			
Product Net Width:	8 mm			
Technical				
Spacing:	8 mm			
Function:	Pre-printed marker card			
Function: Insulation Material:	Polyamide			
Insulation Material:				
Insulation Material: Technical UL/CSA	Polyamide			
Insulation Material: Technical UL/CSA	Polyamide			
Insulation Material: Technical UL/CSA Flammability According to UL94:	Polyamide V2			
Insulation Material: Technical UL/CSA Flammability According to UL94: Environmental	Polyamide V2 Following EU Directive 2002/95/EC August 18, 2005 and amendment			
Insulation Material: Technical UL/CSA Flammability According to UL94:	Polyamide V2			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C			
Insulation Material: <u>Technical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u>	Polyamide V2 Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C (Document Number)			
Insulation Material: Technical UL/CSA Flammability According to UL94: Environmental RoHS Status: Ambient Air Temperature: Certificates and Declarations Declaration of Conformity - CE:	Polyamide V2 Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C (Document Number) 1SND225156C1000			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE:	Polyamide V2 Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C (Document Number)			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u>	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer: ETIM 4:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: Environmental RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer: ETIM 4: ETIM 5:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: Environmental RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer: ETIM 4: ETIM 5:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: Environmental RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer: ETIM 4: ETIM 5: Object Classification Code: <u>Container Information</u>	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block   X			
Insulation Material: <u>Fechnical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer: ETIM 4: ETIM 5: Object Classification Code: <u>Container Information</u> Package Level 1 Width:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   ISND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block   X   120 mm			
Insulation Material: <u>Technical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer: ETIM 4: ETIM 5: Object Classification Code: <u>Container Information</u> Package Level 1 Width: Package Level 1 Length:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block   X   120 mm   200 mm			
Insulation Material: <u>Technical UL/CSA</u> Flammability According to UL94: <u>Environmental</u> RoHS Status: Ambient Air Temperature: <u>Certificates and Declarations</u> Declaration of Conformity - CE: RoHS Information: <u>Classifications</u> E-nummer: ETIM 4: ETIM 5: Object Classification Code: <u>Container Information</u> Package Level 1 Width: Package Level 1 Length: Package Level 1 Gross Weight:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block   X   120 mm   200 mm   0.014 kg			
Insulation Material: Technical UL/CSA Flammability According to UL94: Environmental RoHS Status: Ambient Air Temperature: Certificates and Declarations Declaration of Conformity - CE: RoHS Information: Classifications E-nummer: ETIM 4: ETIM 5: Object Classification Code: Container Information Package Level 1 Width: Package Level 1 Gross Weight: Package Level 1 EAN:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block   X   120 mm   200 mm   0.014 kg   3472591681017			
Insulation Material: Technical UL/CSA Flammability According to UL94: Environmental RoHS Status: Ambient Air Temperature: Certificates and Declarations Declaration of Conformity - CE: RoHS Information: Classifications E-nummer: ETIM 4: ETIM 5: Object Classification Code: Container Information Package Level 1 Width: Package Level 1 Gross Weight: Package Level 1 EAN: Package Level 1 EAN: Package Level 2 Units:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block   X   120 mm   200 mm   0.014 kg   3472591681017   400 piece			
Insulation Material: Technical UL/CSA Flammability According to UL94: Environmental RoHS Status: Ambient Air Temperature: Certificates and Declarations Declaration of Conformity - CE: RoHS Information: Classifications E-nummer: ETIM 4:	Polyamide   V2   Following EU Directive 2002/95/EC August 18, 2005 and amendment   Operation -55 +110 °C   Storage -55 +110 °C   (Document Number)   1SND225156C1000   1SND230504F0204   2967942   EC000761 - Labelling for terminal block   EC000761 - Labelling for terminal block   X   120 mm   200 mm   0.014 kg   3472591681017			







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
MC812PA Terminal Block Markers pre- printed : U1 (x100) Horizontal	1SNK168101R0000	MC812PA (H/ texto)	Buy on EAN