



**Automatzación Eléctrica**  
Especialistas en Automatzación

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	ZS4-PR
Product ID:	1SNK505063R0000
EAN:	3472595050635
Catalog Description:	ZS4-PR Screw Clamp Terminal Block - Feed-through - Purple
Long Description:	ZS4-PR Screw Clamp Terminal Block - Feed-through - Purple, 4mm <sup>2</sup> RatedCrossSection, 5.2mmSpacing, TH 35-7.5, TH 35-15 Rail

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

## Ordering

EAN:	3472595050635
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010

## Dimensions

Product Net Width:	5.2 mm
Product Net Height:	53 mm
Product Net Length:	47.3 mm
Product Net Depth:	47.3 mm
Product Net Weight:	8.8 g

## Container Information

Package Level 1 Units:	50 piece
Package Level 1 Width:	54 mm
Package Level 1 Height:	52 mm
Package Level 1 Length:	252 mm
Package Level 1 Gross Weight:	0.44 kg
Package Level 1 EAN:	3472595050635
Package Level 2 Units:	900 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	200 mm
Package Level 2 Length:	400 mm
Package Level 2 Gross Weight:	8.420 kg
Package Level 3 Units:	43200 piece
Product Packing Type:	Box

## Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 24 ... 12 AWG Screw Clamp / Flexible 2x 24 ... 16 AWG Screw Clamp / Rigid 1x 24 ... 12 AWG Screw Clamp / Rigid 2x 24 ... 16 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 14 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / With Twin Ferrule 2x 24 ... 16 AWG
Connecting Capacity UL/CSA:	Stranded 12 AWG
Flammability According to UL94:	V0
Short-Circuit Current Rating (SCCR):	100 kA

## Additional Information

Ambient Temperature:	-5 ... +40 °C
Color:	Purple
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22 ... 4 mm <sup>2</sup>

Screw Clamp / Flexible 2x 0.2 ... 1.5 mm<sup>2</sup>  
 Screw Clamp / Rigid 1x 0.2 ... 4 mm<sup>2</sup>  
 Screw Clamp / Rigid 2x 0.2 ... 1.5 mm<sup>2</sup>  
 Screw Clamp / With Insulated Ferrule 1x 0.22 ... 2.5 mm<sup>2</sup>  
 Screw Clamp / Without Insulated Ferrule 1x 0.22 ... 4 mm<sup>2</sup>  
 Screw Clamp / With Twin Ferrule 2x 0.22 ... 1.5 mm<sup>2</sup>

<b>Connection Type:</b>	Screw clamp
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>Dielectric Test Voltage:</b>	2200 V
<b>Function:</b>	Feed-through
<b>Gauge Type:</b>	A3-B3
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Insulation Material:</b>	Polyamide
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Number of Levels:</b>	1
<b>Pollution Degree:</b>	3
<b>Power Loss:</b>	1 W
<b>Product Main Type:</b>	ZS4
<b>Product Name:</b>	Terminal Block
<b>Rated Cross-Section:</b>	4 mm <sup>2</sup>
<b>Rated Current (I<sub>n</sub>):</b>	Main Circuit 32 A
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	8000 V
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	for 1 s 480 A
<b>Rated Voltage (U<sub>r</sub>):</b>	1000 V
<b>Recommended Screw Driver:</b>	3.5 mm
<b>RoHS Date:</b>	20050818
<b>Spacing:</b>	5.2 mm
<b>Sub-Function:</b>	2 connections
<b>Sub-Function 3:</b>	2 connections
<b>Wire Stripping Length:</b>	10.5 mm

#### Certificates and Declarations (Document Number)

<b>ATEX Certificate:</b>	1SND162004A1706
<b>BV Certificate:</b>	1SND161073A0203
<b>CB Certificate:</b>	1SND161017A0202
<b>CSA Certificate:</b>	1SND161070A0208
<b>cUL Certificate:</b>	1SND161040A0206
<b>Data Sheet, Technical Information:</b>	1SNK161001D0201
<b>Declaration of Conformity - CE:</b>	1SND225081C1013
<b>DNV Certificate:</b>	1SND161087A0202
<b>RINA Certificate:</b>	1SND161088A0200
<b>RoHS Information:</b>	1SND230491F0206

#### Classifications

<b>E-nummer:</b>	2925906
<b>ETIM 4:</b>	EC000897 - Feed-through terminal block
<b>ETIM 5:</b>	EC000897 - Feed-through terminal block
<b>Object Classification Code:</b>	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
ZS4-PR Screw Clamp Terminal Block - Feed-through - Purple	1SNK505063R0000	ZS4-PR	<a href="#">Buy on EAN</a>