



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

ZS4-WH



Extended Product Type:	ZS4-WH			
Product ID:	1SNK505065R0000			
EAN:	3472595050659			
Catalog Description:	ZS4-WH Screw Clamp Terminal Block - Feed-through - White			
Long Description:	ZS4-WH Screw Clamp Terminal Block - Feed-through - White, 4mm ² RatedCrossSection, 5.2mmSpacing, TH 35-7.5, TH 35-15 Rail			
Catagorias				
Categories	d Systems » Connection Devices » Terminal Blocks » SNK Series			
Products » Low Voltage Products and	D Systems » Connection Devices » Terminal Blocks » SINK Series			
Ordering				
Minimum Order Quantity:	50 piece			
Customs Tariff Number:	85369010			
EAN:	3472595050659			
	34/2353030035			
Dimensions				
Product Net Height:	53 mm			
Product Net Length:	47.3 mm			
Product Net Depth:	47.3 mm			
Product Net Weight:	8.8 g			
Product Net Width:	5.2 mm			
Container Information				
Package Level 1 Width:	54 mm			
Package Level 1 Length:	252 mm			
Package Level 1 Height:	52 mm			
Package Level 1 Gross Weight:	0.44 kg			
Package Level 1 EAN:	3472595050659			
Package Level 2 Units:	900 piece			
Package Level 2 Width:	300 mm			
Package Level 2 Length:	400 mm			
Package Level 2 Height:	200 mm			
Package Level 2 Gross Weight:	8.420 kg			
Package Level 3 Units:	43200 piece			
Product Packing Type:	Box			
Package Level 1 Units:	50 piece			
Technical				
Spacing:	5.2 mm			
Connection Type:	Screw clamp			
Function:	Feed-through			
Number of Levels:	1			
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22 4 mm ² Screw Clamp / Flexible 2x 0.2 1.5 mm ² Screw Clamp / Rigid 1x 0.2 4 mm ² Screw Clamp / Rigid 2x 0.2 1.5 mm ² Screw Clamp / With Insulated Ferrule 1x 0.22 2.5 mm ² Screw Clamp / Without Insulated Ferrule 1x 0.22 4 mm ² Screw Clamp / With Twin Ferrule 2x 0.22 1.5 mm ²			
Gauge Type:	A3-B3			
Rated Current (I _n):	Main Circuit 32 A			
Rated Short-time Withstand Current (I _{cw}):	for 1 s 480 A			
Rated Voltage (U _r):	1000 V			
Rated Impulse Withstand Voltage (U _{imp}):	8000 V			
•	2200 ∨			
Dielectric Test Voltage:	2200 V			

acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

3

1 W

Polyamide

Pollution Degree: Power Loss:

Degree of Protection:

Mounting on DIN Rail:

Insulation Material:

	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715			
Wire Stripping Length:	10.5 mm			
Recommended Screw Driver:	3.5 mm			
Rated Cross-Section:	4 mm ²			
Technical UL/CSA				
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 24 12 AWG Screw Clamp / Flexible 2x 24 16 AWG Screw Clamp / Rigid 1x 24 12 AWG Screw Clamp / Rigid 2x 24 16 AWG Screw Clamp / With Insulated Ferrule 1x 24 14 AWG Screw Clamp / Without Insulated Ferrule 1x 24 12 AWG Screw Clamp / Without Insulated Ferrule 2x 24 16 AWG			
Connecting Capacity UL/CSA:	Stranded 12 AWG			
Flammability According to UL94:	VO			
Short-Circuit Current Rating (SCCR):	100 kA			
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V			
Environmental				
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant			
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment			
Ambient Air Temperature:	Operation -55 +110 °C			
	Storage -55 +110 °C			
Certificates and Declarations (Document Number)				
ATEX Certificate:	1SND162004A1706			
BV Certificate:	1SND161073A0203			
CB Certificate:	1SND161017A0202			
CSA Certificate:	1SND161070A0208			
cUL Certificate:	1SND161040A0206			
Declaration of Conformity - CE:	1SND225081C1013			
-				
DNV Certificate:	1SND161087A0202			

Classifications

RINA Certificate:

RoHS Information:

E-nummer:	2925908
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X

1SND161088A0200

1SND230491F0206







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
ZS4-WH Screw Clamp Terminal Block - Feed- through - White	1SNK505065R0000	ZS4-WH	Buy on EAN