



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE



### **General Information**

Extended Product Type: ZS6-D1

 Product ID:
 1SNK506211R0000

 EAN:
 3472595062119

Catalog Description: ZS6-D1 Screw Clamp Terminal Block - Double Deck - Grey

Long Description: ZS6-D1 Screw Clamp Terminal Block - Double Deck - Grey, 4mm² RatedCrossSection,

6mmSpacing, TH 35-7.5, TH 35-15 Rail

# Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

### Ordering

Minimum Order Quantity:50 pieceCustoms Tariff Number:85369010EAN:3472595062119

### **Dimensions**

Product Net Height: 70.4 mm

Product Net Length: 65.5 mm

Product Net Depth: 65.5 mm

Product Net Weight: 18.4 g

Product Net Width: 6 mm

### **Container Information**

Package Level 1 Width: 61 mm Package Level 1 Length: 353 mm Package Level 1 Height: 67 mm Package Level 1 Gross Weight: 0.92 kg Package Level 1 EAN: 3472595062119 Package Level 2 Units: 400 piece Package Level 2 Width: 300 mm Package Level 2 Length: 400 mm Package Level 2 Height: 200 mm Package Level 2 Gross Weight: 7.860 kg Package Level 3 Units: 19200 piece **Product Packing Type:** Box Package Level 1 Units: 50 piece

## **Technical**

Spacing:6 mmConnection Type:Screw clampFunction:Feed-through

Number of Levels: 2

Connecting Capacity-Main Circuit: Screw Clamp / Flexible 1x 0.2 ... 6 mm<sup>2</sup>

Screw Clamp / Flexible 2x 0.2 ... 2.5 mm<sup>2</sup> Screw Clamp / Rigid 1x 0.2 ... 6 mm<sup>2</sup> Screw Clamp / Rigid 2x 0.2 ... 2.5 mm<sup>2</sup>

Screw Clamp / With Insulated Ferrule 1x 0.22 ... 4 mm<sup>2</sup> Screw Clamp / Without Insulated Ferrule 1x 0.22 ... 4 mm<sup>2</sup> Screw Clamp / With Twin Ferrule 2x 0.22 ... 2.5 mm<sup>2</sup>

Gauge Type: A4-B3

Rated Current (I<sub>n</sub>): Main Circuit 40 A Rated Short-time Withstand Current for 1 s 720 A

(I<sub>cw</sub>):

800 V

Rated Voltage (U<sub>r</sub>):

Rated Impulse Withstand Voltage

(U<sub>imp</sub>):

8000 V

Dielectric Test Voltage: 2000 V
Pollution Degree: 3
Power Loss: 2.6 W

Degree of Protection: acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

Insulation Material: Polyamide

**Mounting on DIN Rail:** TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

Wire Stripping Length: 10.0 mm

Recommended Screw Driver: 4 mm

Rated Cross-Section: 6 mm<sup>2</sup>

## **Technical UL/CSA**

**Connecting Capacity Main Circuit** 

UL/CSA:

Screw Clamp / Flexible 1x 24 ... 10 AWG Screw Clamp / Flexible 2x 24 ... 14 AWG Screw Clamp / Rigid 1x 24 ... 10 AWG Screw Clamp / Rigid 2x 24 ... 14 AWG

Screw Clamp / With Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / With Twin Ferrule 2x 24 ... 14 AWG

Connecting Capacity UL/CSA: Stranded 10 AWG

Flammability According to UL94: V0 Short-Circuit Current Rating (SCCR): 100 kA

**Maximum Operating Voltage** 

UL/CSA:

Main Circuit 300 V

### **Environmental**

Resistance to Vibrations acc. to IEC Compliant

60068-2-6:

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C

Storage -55 ... +110 °C

## **Certificates and Declarations (Document Number)**

**ATEX Certificate:** 1SND162004A1706 **BV Certificate:** 1SND161073A0203 **CB Certificate:** 1SND161026A0204 **CSA Certificate:** 1SND161070A0208 **cUL Certificate:** 1SND161040A0206 **Declaration of Conformity - CE:** 1SND225081C1013 **DNV Certificate:** 1SND161087A0202 **RINA Certificate:** 1SND161088A0200 **RoHS Information:** 1SND230491F0206

### Classifications

E-nummer: 2925936

ETIM 4: EC000897 - Feed-through terminal block

ETIM 5: EC000897 - Feed-through terminal block

Object Classification Code: X







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
ZS6-D1 Screw Clamp Terminal Block - Double Deck - Grey	1SNK506211R0000	ZS6-D1	Buy on EAN