



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	ZS4-S-T2.3-R1
Product ID:	1SNK506312R0000
EAN:	3472595063123
Catalog Description:	ZS4-S-T2.3-R1 Screw Clamp Terminal Block - Disconnect with blade - Grey - with 2 test socket screws DIA 2.3 mm 0.091 in
Long Description:	ZS4-S-T2.3-R1 Screw Clamp Terminal Block - Disconnect with Blade - Grey - with 2 test socket screws DIA 2,3 mm .091 in, 4mm ² RatedCrossSection, 6mmSpacing, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

Ordering

Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
EAN:	3472595063123

Dimensions

Product Net Height:	70.5 mm
Product Net Length:	51.35 mm
Product Net Depth:	51.4 mm
Product Net Weight:	14.2 g
Product Net Width:	6 mm

Container Information

Package Level 1 Width:	61 mm
Package Level 1 Length:	339 mm
Package Level 1 Height:	52 mm
Package Level 1 Gross Weight:	0.725 kg
Package Level 1 EAN:	3472595063123
Package Level 2 Units:	600 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	400 mm
Package Level 2 Height:	200 mm
Package Level 2 Gross Weight:	9.020 kg
Package Level 3 Units:	28800 piece
Product Packing Type:	Box
Package Level 1 Units:	50 piece

Technical

Spacing:	6 mm
Connection Type:	Screw clamp
Function:	Disconnect
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.22 ... 4 mm ² Screw Clamp / Flexible 2x 0.2 ... 1.5 mm ² Screw Clamp / Rigid 1x 0.2 ... 4 mm ² Screw Clamp / Rigid 2x 0.2 ... 1.5 mm ² Screw Clamp / With Insulated Ferrule 1x 0.22 ... 4 mm ² Screw Clamp / Without Insulated Ferrule 1x 0.22 ... 4 mm ² Screw Clamp / With Twin Ferrule 2x 0.22 ... 1.5 mm ²
Gauge Type:	A3-B3
Rated Current (I _n):	Main Circuit 26 A
Rated Short-time Withstand Current (I _{cw}):	for 1 s 480 A
Rated Voltage (U _r):	400 V
Rated Impulse Withstand Voltage (U _{imp}):	6000 V
Dielectric Test Voltage:	1890 V
Pollution Degree:	3
Power Loss:	0.8 W
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20

Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	10.5 mm
Recommended Screw Driver:	3.5 mm
Rated Cross-Section:	4 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 24 ... 10 AWG Screw Clamp / Flexible 2x 24 ... 16 AWG Screw Clamp / Rigid 1x 24 ... 10 AWG Screw Clamp / Rigid 2x 24 ... 16 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / With Twin Ferrule 2x 24 ... 16 AWG
Connecting Capacity UL/CSA:	Stranded 10 AWG
Flammability According to UL94:	V0
Maximum Operating Voltage UL/CSA:	Main Circuit 150 V

Environmental

Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

BV Certificate:	1SND161073A0203
CB Certificate:	1SND161077A0201
CSA Certificate:	1SND161070A0208
cUL Certificate:	1SND161040A0206
Declaration of Conformity - CE:	1SND225099C1005
DNV Certificate:	1SND161087A0202
EAC Certificate:	1SND161009A1100
RINA Certificate:	1SND161088A0200
RoHS Information:	1SND230491F0206

Classifications

E-number:	2925941
ETIM 4:	EC000902 - (Knife) disconnect terminal block
ETIM 5:	EC000902 - (Knife) disconnect terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
ZS4-S-T2.3-R1 Screw Clamp Terminal Block - Disconnect with blade - Grey - with 2 test socket screws DIA 2.3 mm 0.091 in	1SNK506312R0000	ZS4-S-T2.3-R1	Buy on EAN