



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

| | |
|------------------------|--|
| Extended Product Type: | ZS4-S-R3 |
| Product ID: | 1SNK508416R0000 |
| EAN: | 3472595084166 |
| Catalog Description: | ZS4-S-R3 Screw Clamp Terminal Block - Disconnect with Lever - Grey |
| Long Description: | ZS4-S-R3 Screw Clamp Terminal Block - Disconnect with Lever - Grey, 4mm ² RatedCrossSection, 8mmSpacing, TH 35-7.5, TH 35-15 Rail |

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

Ordering

| | |
|-------------------------|--------------|
| Minimum Order Quantity: | 50 piece |
| Customs Tariff Number: | 85369010 |
| Color: | Grey, Orange |

Dimensions

| | |
|---------------------|---------|
| Product Net Height: | 59.7 mm |
| Product Net Length: | 45.6 mm |
| Product Net Depth: | 45.6 mm |
| Product Net Weight: | 13.3 g |
| Product Net Width: | 8 mm |

Technical

| | |
|--|---|
| Spacing: | 8 mm |
| Connection Type: | Screw clamp |
| Function: | Disconnect |
| Number of Levels: | 1 |
| Connecting Capacity-Main Circuit: | Screw Clamp / Flexible 1x 0.22 ... 4 mm ² Screw Clamp / Flexible 2x 0.2 ... 2.5 mm ² Screw Clamp / Rigid 1x 0.2 ... 4 mm ² Screw Clamp / Rigid 2x 0.2 ... 2.5 mm ² Screw Clamp / With Insulated Ferrule 1x 0.22 ... 4 mm ² Screw Clamp / Without Insulated Ferrule 1x 0.22 ... 4 mm ² Screw Clamp / With Twin Ferrule 2x 0.22 ... 2.5 mm ² |
| Gauge Type: | A3-B3 |
| Rated Current (I _n): | Main Circuit 18 A |
| Rated Short-time Withstand Current (I _{cw}): | for 1 s 300 A |
| Rated Voltage (U _r): | 630 V |
| Rated Impulse Withstand Voltage (U _{imp}): | 6000 V |
| Dielectric Test Voltage: | 2200 V |
| Pollution Degree: | 3 |
| Power Loss: | 0.6 W |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material: | Polyamide |
| Mounting on DIN Rail: | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Wire Stripping Length: | 11.0 mm |
| Recommended Screw Driver: | 3.5 mm |
| Rated Cross-Section: | 2.5 mm ² |

Technical UL/CSA

| | |
|--|---|
| Connecting Capacity Main Circuit UL/CSA: | Screw Clamp / Flexible 1x 24 ... 10 AWG Screw Clamp / Flexible 2x 24 ... 14 AWG Screw Clamp / Rigid 1x 24 ... 10 AWG Screw Clamp / Rigid 2x 24 ... 14 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / With Twin Ferrule 2x 24 ... 14 AWG |
| Connecting Capacity UL/CSA: | Stranded 10 AWG |
| Flammability According to UL94: | V0 |
| Maximum Operating Voltage | Main Circuit 300 V |

UL/CSA:

Environmental

Resistance to Vibrations acc. to IEC 60068-2-6: Compliant

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C
Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

BV Certificate: 1SND161073A0203

CSA Certificate: 1SND161070A0208

cUL Certificate: 1SND161040A0206

Declaration of Conformity - CE: 1SND225099C1005

DNV Certificate: 1SND161087A0202

EAC Certificate: 1SND161009A1100

RINA Certificate: 1SND161088A0200

RoHS Information: 1SND230491F0206

Classifications

E-nummer: 2925973

ETIM 4: EC000902 - (Knife) disconnect terminal block

ETIM 5: EC000902 - (Knife) disconnect terminal block

Object Classification Code: X

Container Information

Package Level 1 Width: 119 mm

Package Level 1 Length: 201 mm

Package Level 1 Height: 46 mm

Package Level 1 Gross Weight: 0.665 kg

Package Level 1 EAN: 3472595084166

Package Level 2 Units: 450 piece

Package Level 2 Width: 300 mm

Package Level 2 Length: 400 mm

Package Level 2 Height: 200 mm

Package Level 2 Gross Weight: 6.530 kg

Package Level 3 Units: 21600 piece

Product Packing Type: Box

Package Level 1 Units: 50 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|--|-----------------|------------------|----------------------------|
| ZS4-S-R3 Screw Clamp Terminal Block - Disconnect with Lever - Grey | 1SNK508416R0000 | ZS4-S-R3 | Buy on EAN |