



Automatización Eléctrica Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking <u>HERE</u>

ZS16



Extended Product Type:	ZS16			
Product ID:	1SNK510010R0000			
EAN:	3472595100101			
Catalog Description:	ZS16 Screw Clamp Terminal Block - Feed-through - Grey			
Long Description:	ZS16 Screw Clamp Terminal Block - Feed-through - Grey, 16mm ² RatedCrossSection 10mmSpacing, TH 35-7.5, TH 35-15 Rail			
Categories				
	d Systems » Connection Devices » Terminal Blocks » SNK Series			
Drdering				
Minimum Order Quantity:	25 piece			
Customs Tariff Number:	85369010			
EAN:	3472595100101			
Dimensions				
Product Net Height:	56.1 mm			
Product Net Length:	48.8 mm			
Product Net Depth:	48.8 mm			
Product Net Weight:	20.2 g			
Product Net Width:	10 mm			
Dentalment laft ti				
Container Information	F0			
Package Level 1 Width:	52 mm			
Package Level 1 Length:	259 mm			
Package Level 1 Height:	50 mm			
Package Level 1 Gross Weight:	0.505 kg			
Package Level 1 EAN:	3472595100101			
Package Level 2 Units:	450 piece			
Package Level 2 Width:	300 mm			
Package Level 2 Length:	400 mm			
Package Level 2 Height:	200 mm			
Package Level 2 Gross Weight:	9.680 kg			
Package Level 3 Units:	21600 piece			
Product Packing Type:	Box			
Package Level 1 Units:	25 piece			
Fechnical				
Spacing:	10 mm			
Connection Type:	Screw clamp			
Function:	Feed-through			
Number of Levels:	1			
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 16 mm ² Screw Clamp / Flexible 2x 0.5 6 mm ² Screw Clamp / Rigid 1x 0.5 16 mm ² Screw Clamp / Rigid 2x 0.5 6 mm ² Screw Clamp / With Insulated Ferrule 1x 0.5 10 mm ² Screw Clamp / Without Insulated Ferrule 1x 0.5 16 mm ² Screw Clamp / Without Insulated Ferrule 2x 0.5 6 mm ²			
Gauge Type:	A6-B6			
Rated Current (I _n):	Main Circuit 76 A			
Rated Short-time Withstand Current (I _{cw}):	for 1 s 1920 A			
Rated Voltage (U _r):	1000 V			
Rated Impulse Withstand Voltage (U _{imp}):	8000 V			
Dielectric Test Voltage:	2200 V			
Pollution Degree:	3			
Power Loss:	2.4 W			
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20			
Insulation Material:	Polyamide			
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715			

	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715			
Wire Stripping Length:	13.5 mm			
Recommended Screw Driver:	5.5 mm			
Rated Cross-Section:	16 mm ²			
Technical UL/CSA				
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 24 4 AWG Screw Clamp / Flexible 2x 20 10 AWG Screw Clamp / Rigid 1x 24 4 AWG Screw Clamp / Rigid 2x 20 10 AWG Screw Clamp / With Insulated Ferrule 1x 24 8 AWG Screw Clamp / Without Insulated Ferrule 1x 24 4 AWG Screw Clamp / Without Insulated Ferrule 1x 24 4 AWG			
Connecting Capacity UL/CSA:	Stranded 4 AWG			
Flammability According to UL94:	VO			
Short-Circuit Current Rating (SCCR): 100 kA			
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V			
Fuerding service set of				
Environmental Resistance to Vibrations acc. to IEC	C Compliant			
Resistance to Vibrations acc. to IEC 60068-2-6:	•			
Resistance to Vibrations acc. to IEC	Compliant Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C			
Resistance to Vibrations acc. to IE 60068-2-6: RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D ATEX Certificate:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C Occument Number) 1SND162004A1706			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D ATEX Certificate: BV Certificate: CB Certificate:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C Occument Number) 1SND162004A1706 1SND161073A0203			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D ATEX Certificate: BV Certificate: CB Certificate:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C Pocument Number) 1SND162004A1706 1SND161073A0203 1SND161021A0201			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D ATEX Certificate: BV Certificate: CB Certificate: CSA Certificate: cUL Certificate:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C Document Number) 1SND162004A1706 1SND161073A0203 1SND161021A0201 1SND161070A0208			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D ATEX Certificate: BV Certificate: CB Certificate: CSA Certificate: cUL Certificate:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C Pocument Number) 1SND162004A1706 1SND161073A0203 1SND161021A0201 1SND161070A0208 1SND161040A0206			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D ATEX Certificate: BV Certificate: CB Certificate: CSA Certificate: cUL Certificate: Declaration of Conformity - CE:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C Pocument Number) 1SND162004A1706 1SND161073A0203 1SND161021A0201 1SND161070A0208 1SND161040A0206 1SND225081C1013			
Resistance to Vibrations acc. to IEC 60068-2-6: RoHS Status: Ambient Air Temperature: Certificates and Declarations (D ATEX Certificate: BV Certificate: CB Certificate: CSA Certificate: cUL Certificate: Declaration of Conformity - CE: DNV Certificate:	Following EU Directive 2002/95/EC August 18, 2005 and amendment Operation -55 +110 °C Storage -55 +110 °C Pocument Number) 1SND162004A1706 1SND161073A0203 1SND161021A0201 1SND161070A0208 1SND161040A0206 1SND225081C1013 1SND161087A0202			

Classifications

E-nummer:	2925974
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
ZS16 Screw Clamp Terminal Block - Feed- through - Grey	1SNK510010R0000	ZS16	Buy on EAN