



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	ZS25-BL
Product ID:	1SNK512020R0000
EAN:	3472595120208
Catalog Description:	ZS25-BL Screw Clamp Terminal Block - Feed-through - Blue
Long Description:	ZS25-BL Screw Clamp Terminal Block - Feed-through - Blue - 25 mm <sup>2</sup> - 12 mm 0.472 in spacing - Flat marking area

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

## Ordering

Minimum Order Quantity:	25 piece
Customs Tariff Number:	85369010
Color:	Blue

## Dimensions

Product Net Height:	56.1 mm
Product Net Length:	48.8 mm
Product Net Depth:	48.8 mm
Product Net Weight:	21.4 g
Product Net Width:	12 mm

## Technical

Spacing:	12 mm
Connection Type:	Screw clamp
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 25 mm <sup>2</sup> Screw Clamp / Flexible 2x 0.5 ... 10 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 25 mm <sup>2</sup> Screw Clamp / Rigid 2x 0.5 ... 10 mm <sup>2</sup> Screw Clamp / With Insulated Ferrule 1x 0.5 ... 16 mm <sup>2</sup> Screw Clamp / Without Insulated Ferrule 1x 0.5 ... 16 mm <sup>2</sup> Screw Clamp / With Twin Ferrule 2x 0.5 ... 10 mm <sup>2</sup>
Gauge Type:	A6-B6
Rated Current (I <sub>n</sub> ):	Main Circuit 76 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 1920 A
Rated Voltage (U <sub>r</sub> ):	1000 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8000 V
Dielectric Test Voltage:	2200 V
Pollution Degree:	3
Power Loss:	2.4 W
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	13.5 mm
Rated Cross-Section:	16 mm <sup>2</sup>

## Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 24 ... 3 AWG Screw Clamp / Rigid 2x 20 ... 10 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 8 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 4 AWG Screw Clamp / With Twin Ferrule 2x 20 ... 10 AWG
Connecting Capacity UL/CSA:	Stranded 3 AWG
Flammability According to UL94:	V0
Short-Circuit Current Rating (SCCR):	100 kA
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V

## Environmental

Resistance to Vibrations acc. to IEC 60068-2-6: Compliant

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Ambient Air Temperature: Operation -55 ... +110 °C  
Storage -55 ... +110 °C

## Certificates and Declarations (Document Number)

ATEX Certificate: 1SND162004A1706

BV Certificate: 1SND161073A0203

CB Certificate: 1SND161100A0202

CSA Certificate: 1SND161070A0208

cUL Certificate: 1SND161041A0207

Declaration of Conformity - CE: 1SND225081C1013

DNV Certificate: 1SND161087A0202

RoHS Information: 1SND230491F0206

## Classifications

ETIM 4: EC000897 - Feed-through terminal block

ETIM 5: EC000897 - Feed-through terminal block

Object Classification Code: X

## Container Information

Package Level 1 Width: 62 mm

Package Level 1 Length: 280 mm

Package Level 1 Height: 64 mm

Package Level 1 Gross Weight: 0.56 kg

Package Level 1 EAN: 3472595120208

Package Level 2 Units: 200 piece

Package Level 2 Width: 300 mm

Package Level 2 Length: 400 mm

Package Level 2 Height: 200 mm

Package Level 2 Gross Weight: 4.480 kg

Package Level 3 Units: 9600 piece

Product Packing Type: Box

Package Level 1 Units: 25 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
ZS25-BL Screw Clamp Terminal Block - Feed-through - Blue	1SNK512020R0000	ZS25-BL	<a href="#">Buy on EAN</a>