



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

## General Information

Extended Product Type:	ZS25-PE
Product ID:	1SNK512150R0000
EAN:	3472595121502
Catalog Description:	ZS25-PE Screw Clamp Terminal Block - Ground - Green/Yellow
Long Description:	ZS25-PE Screw Clamp Terminal Block - Ground - Green/Yellow - 25 mm <sup>2</sup> - 12 mm 0.472 in spacing - Flat marking area

## Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

## Ordering

Minimum Order Quantity:	20 piece
Customs Tariff Number:	85369010
EAN:	3472595121502

## Dimensions

Product Net Height:	63.6 mm
Product Net Length:	48.9 mm
Product Net Depth:	48.9 mm
Product Net Weight:	38 g
Product Net Width:	12 mm

## Container Information

Package Level 1 Width:	62 mm
Package Level 1 Length:	252 mm
Package Level 1 Height:	52 mm
Package Level 1 Gross Weight:	0.78 kg
Package Level 1 EAN:	3472595121502
Package Level 2 Units:	300 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	400 mm
Package Level 2 Height:	200 mm
Package Level 2 Gross Weight:	11.700 kg
Package Level 3 Units:	14400 piece
Product Packing Type:	Box
Package Level 1 Units:	20 piece

## Technical

Spacing:	12 mm
Connection Type:	Screw clamp
Function:	Ground
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 25 mm <sup>2</sup> Screw Clamp / Flexible 2x 0.5 ... 10 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 25 mm <sup>2</sup> Screw Clamp / Rigid 2x 0.5 ... 10 mm <sup>2</sup> Screw Clamp / With Insulated Ferrule 1x 0.5 ... 16 mm <sup>2</sup> Screw Clamp / Without Insulated Ferrule 1x 0.5 ... 16 mm <sup>2</sup> Screw Clamp / With Twin Ferrule 2x 0.5 ... 10 mm <sup>2</sup>
Gauge Type:	A6-B6
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 1920 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8000 V
Dielectric Test Voltage:	2200 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	13.5 mm
Rated Cross-Section:	16 mm <sup>2</sup>

## Technical UL/CSA

<b>Connecting Capacity Main Circuit UL/CSA:</b>	Screw Clamp / Rigid 1x 24 ... 3 AWG Screw Clamp / Rigid 2x 20 ... 10 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 8 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 4 AWG Screw Clamp / With Twin Ferrule 2x 20 ... 10 AWG
<b>Connecting Capacity UL/CSA:</b>	Stranded 3 AWG
<b>Flammability According to UL94:</b>	V0

## Environmental

<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	Compliant
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment
<b>Ambient Air Temperature:</b>	Operation -55 ... +110 °C Storage -55 ... +110 °C

## Certificates and Declarations (Document Number)

<b>ATEX Certificate:</b>	1SND162004A1706
<b>BV Certificate:</b>	1SND161073A0203
<b>CB Certificate:</b>	1SND161101A0200
<b>CSA Certificate:</b>	1SND161070A0208
<b>cUL Certificate:</b>	1SND161041A0207
<b>Declaration of Conformity - CE:</b>	1SND225094C1007
<b>DNV Certificate:</b>	1SND161087A0202
<b>RoHS Information:</b>	1SND230491F0206

## Classifications

<b>ETIM 4:</b>	EC000901 - Ground terminal block
<b>ETIM 5:</b>	EC000901 - Ground terminal block
<b>Object Classification Code:</b>	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
ZS25-PE Screw Clamp Terminal Block - Ground - Green/Yellow	1SNK512150R0000	ZS25-PE	<a href="#">Buy on EAN</a>