At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE

ZS95-BL

ABB

General Information

Extended Product Type:	ZS95-BL
Product ID:	1SNK526020R0000
EAN:	3472595260201
Catalog Description:	ZS95-BL Screw Clamp Terminal Block - Feed-through - Blue
Long Description:	ZS95-BL Screw Clamp Terminal Block - Feed-through - Blue, 95mm² RatedCrossSection, 26mmSpacing, TH 35-7.5, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

Ordering

Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369010
Color:	Blue

Dimensions

Product Net Height:	87 mm
Product Net Length:	80.1 mm
Product Net Depth:	80.1 mm
Product Net Weight:	215.1 g
Product Net Width:	26 mm

Technical

Spacing:	26 mm
Connection Type:	Screw clamp
Function:	Feed-through
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 35 ... 95 mm² Screw Clamp / Flexible 2x 25 ... 35 mm² Screw Clamp / Rigid 1x 35 ... 120 mm² Screw Clamp / Rigid 2x 25 ... 35 mm² Screw Clamp / With Insulated Ferrrule 1x 35 ... 50 mm² Screw Clamp / Without Insulated Ferrule 1x 35 ... 50 mm² Screw Clamp / With Twin Ferrule 2x 16 mm²
Gauge Type:	B12
Rated Current (I_n):	Main Circuit 232 A
Rated Short-time Withstand Current (I_{cw}):	for 1 s 11400 A
Rated Voltage (U_r):	1000 V
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Dielectric Test Voltage:	3500 V
Pollution Degree:	3
Power Loss:	7.4 W
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	26.0 mm
Recommended Screw Driver:	6 mm
Rated Cross-Section:	95 mm²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 2 ... 0000 AWG Screw Clamp / Flexible 2x 4 ... 2 AWG Screw Clamp / Rigid 1x 2 ... 0000 AWG Screw Clamp / Rigid 2x 4 ... 2 AWG Screw Clamp / With Twin Ferrule 2x 6 AWG
Connecting Capacity UL/CSA:	Stranded 0 AWG
Flammability According to UL94:	V0
Short-Circuit Current Rating (SCCR):	100 kA
Maximum Operating Voltage UL/CSA:	Main Circuit 1000 V

Environmental

Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

ATEX Certificate:	1SND162004A1706
BV Certificate:	1SND161073A0203
CB Certificate:	1SND161032A0201
CSA Certificate:	1SND161067A0201
cUL Certificate:	1SND161041A0207
Declaration of Conformity - CE:	1SND225081C1013
DNV Certificate:	1SND161087A0202
RINA Certificate:	1SND161088A0200
RoHS Information:	1SND230491F0206

Classifications

E-nummer:	2925986
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
Object Classification Code:	X

Container Information

Package Level 1 Width:	135 mm
Package Level 1 Length:	177 mm
Package Level 1 Height:	87 mm
Package Level 1 Gross Weight:	2.151 kg
Package Level 1 EAN:	3472595260201
Package Level 2 Units:	30 piece
Package Level 2 Width:	200 mm
Package Level 2 Length:	300 mm
Package Level 2 Height:	200 mm
Package Level 2 Gross Weight:	6.700 kg
Package Level 3 Units:	2880 piece
Product Packing Type:	Box
Package Level 1 Units:	10 piece

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
ZS95-BL Screw Clamp Terminal Block - Feed-through - Blue	1SNK526020R0000	ZS95-BL	Buy on EAN