



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	ZS95-PE
Product ID:	1SNK526150R0000
EAN:	3472595261505
Catalog Description:	ZS95-PE Screw Clamp Terminal Block - Ground - Green/Yellow
Long Description:	ZS95-PE Screw Clamp Terminal Block - Ground - Green/Yellow, 95mm ² RatedCrossSection, 26mmSpacing, TH 35-15 Rail

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

Ordering

Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369010
EAN:	3472595261505

Dimensions

Product Net Height:	87 mm
Product Net Length:	85.2 mm
Product Net Depth:	85.2 mm
Product Net Weight:	278 g
Product Net Width:	26 mm

Container Information

Package Level 1 Width:	135 mm
Package Level 1 Length:	177 mm
Package Level 1 Height:	87 mm
Package Level 1 Gross Weight:	2.78 kg
Package Level 1 EAN:	3472595261505
Package Level 2 Units:	30 piece
Package Level 2 Width:	200 mm
Package Level 2 Length:	300 mm
Package Level 2 Height:	200 mm
Package Level 2 Gross Weight:	8.590 kg
Package Level 3 Units:	2880 piece
Product Packing Type:	Box
Package Level 1 Units:	10 piece

Technical

Spacing:	26 mm
Connection Type:	Screw clamp
Function:	Ground
Number of Levels:	1
Connecting Capacity-Main Circuit:	Screw Clamp / Flexible 1x 35 ... 95 mm ² Screw Clamp / Rigid 1x 35 ... 120 mm ² Screw Clamp / With Insulated Ferrule 1x 35 ... 50 mm ² Screw Clamp / Without Insulated Ferrule 1x 35 ... 50 mm ²
Gauge Type:	B12
Rated Short-time Withstand Current (I _{cw}):	for 1 s 11400 A
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Dielectric Test Voltage:	3500 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	26.0 mm
Recommended Screw Driver:	6 mm
Rated Cross-Section:	95 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 2 ... 0000 AWG Screw Clamp / Rigid 1x 2 ... 0000 AWG
Connecting Capacity UL/CSA:	Stranded 0 AWG
Flammability According to UL94:	V0

Environmental

Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

ATEX Certificate:	1SND162004A1706
BV Certificate:	1SND161073A0203
CB Certificate:	1SND161033A0201
CSA Certificate:	1SND161070A0208
cUL Certificate:	1SND161040A0206
Declaration of Conformity - CE:	1SND225094C1007
DNV Certificate:	1SND161087A0202
RINA Certificate:	1SND161088A0200
RoHS Information:	1SND230491F0206

Classifications

E-number:	2925987
ETIM 4:	EC000901 - Ground terminal block
ETIM 5:	EC000901 - Ground terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
ZS95-PE Screw Clamp Terminal Block - Ground - Green/Yellow	1SNK526150R0000	ZS95-PE	Buy on EAN