



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	ZK2.5-SF-R3
Product ID:	1SNK706412R0000
EAN:	3472597064128
Catalog Description:	ZK2.5-SF-R3 PI-Spring Clamp Terminal Block - for Fuses 5x20 mm - Grey
Long Description:	ZK2.5-SF-R3 PI-Spring Clamp Terminal Block - for Fuses 5x20 mm - Grey - 2,5 mm ² - 6 mm 0.236 in spacing - Flat marking area

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

Ordering

EAN:	3472597064128
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010

Dimensions

Product Net Width:	6 mm
Product Net Height:	63.1 mm
Product Net Length:	72.5 mm
Product Net Depth:	72.5 mm
Product Net Weight:	16.3 g

Container Information

Package Level 1 Units:	50 piece
Package Level 1 Width:	138 mm
Package Level 1 Height:	78 mm
Package Level 1 Length:	151 mm
Package Level 1 Gross Weight:	0.865 kg
Package Level 1 EAN:	3472597064128
Package Level 2 Units:	400 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	200 mm
Package Level 2 Length:	400 mm
Package Level 2 Gross Weight:	6.920 kg
Package Level 3 Units:	19200 piece
Product Packing Type:	Box

Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Status:	Following EU Directive 2011/65/EC

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 300 V
Connecting Capacity Main Circuit UL/CSA:	Spring Clamp / Rigid 1x 26 ... 12 AWG Spring Clamp / With Insulated Ferrule 1x 26 ... 14 AWG Spring Clamp / Without Insulated Ferrule 1x 26 ... 14 AWG
Connecting Capacity UL/CSA:	Stranded 12 AWG
Flammability According to UL94:	V0

Additional Information

Ambient Temperature:	-5 ... +40 °C
Color:	Grey, Dark Grey
Connecting Capacity-Main Circuit:	Spring Clamp / Flexible 1x 0.22 ... 2.5 mm ² Spring Clamp / Rigid 1x 0.2 ... 4 mm ² Spring Clamp / With Insulated Ferrule 1x 0.22 ... 2.5 mm ² Spring Clamp / Without Insulated Ferrule 1x 0.22 ... 2.5 mm ² Spring Clamp / With Twin Ferrule 2x 0.22 ... 0.5 mm ²
Connection Type:	PI Spring

Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Function:	Fuse
Gauge Type:	A2 / 2.3 mm Dia.
IIT Publishing Status:	Level 0 - Information enabled
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting Type:	The fuse holder must be first disconnected prior any fuse replacement. Mount your fuse safely without touching any active part: put the fuse into the hooks of the fuse holder shutter; at the closing of the shutter, the fuse is perfectly in place in the fuse holder.
Number of Levels:	1
Pollution Degree:	3
Power Loss:	1.6 W
Product Main Type:	ZK2.5-SF-R
Product Name:	Terminal Block
Rated Cross-Section:	2.5 mm ²
Rated Current (I_n):	Main Circuit 6.3 A
Rated Impulse Withstand Voltage (U_{imp}):	6000 V
Rated Voltage (U_r):	500 V
RoHS Date:	20110608
Spacing:	6 mm
Sub-Function:	with blown fuse indicator 115 ... 250 V AC / DC
Sub-Function 3:	For 5x20 Fuses
Sub-Function 4:	With blown fuse indicator LED
Wire Stripping Length:	11.0 mm

Certificates and Declarations (Document Number)

BV Certificate:	1SND162013A0201
CB Certificate:	1SND162010A0200
CSA Certificate:	1SND162014A0203
cUL Certificate:	1SND162012A0202
Data Sheet, Technical Information:	1SNK162045D0201
Declaration of Conformity - CE:	1SND225152C1000
DNV Certificate:	1SND162023A0200
EAC Certificate:	1SND162001A1100
RoHS Information:	1SND230535F0201

Classifications

ETIM 4:	EC000899 - Fuse terminal block
ETIM 5:	EC000899 - Fuse terminal block
Object Classification Code:	X



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
ZK2.5-SF-R3 PI-Spring Clamp Terminal Block - for Fuses 5x20 mm - Grey	1SNK706412R0000	ZK2.5-SF-R3	Buy on EAN