



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#)

General Information

Extended Product Type:	ZK10-PE-3P
Product ID:	1SNK710151R0000
EAN:	3472597101519
Catalog Description:	ZK10-PE-3P PI-Spring clamp Terminal Block - Ground - Green Yellow - 10 mm ² - 10 mm 0.394 in spacing - Flat marking area
Long Description:	ZK10-PE-3P PI-Spring clamp Terminal Block - Ground - Green Yellow - 10 mm ² - 10 mm 0.394 in spacing - Flat marking area

Categories

Products » Low Voltage Products and Systems » Connection Devices » Terminal Blocks » SNK Series

Ordering

Minimum Order Quantity:	20 piece
Customs Tariff Number:	85369010
Color:	Green-Yellow

Dimensions

Product Net Height:	99.1 mm
Product Net Depth:	47.5 mm
Product Net Weight:	43.3 g
Product Net Width:	10 mm

Technical

Spacing:	10 mm
Connection Type:	PI Spring
Function:	Ground
Number of Levels:	1
Connecting Capacity-Main Circuit:	Spring Clamp / Flexible 1x 0.5 ... 10 mm ² Spring Clamp / Rigid 1x 0.5 ... 16 mm ² Spring Clamp / With Insulated Ferrule 1x 0.5 ... 10 mm ² Spring Clamp / Without Insulated Ferrule 1x 0.5 ... 10 mm ² Spring Clamp / With Twin Ferrule 2x 0.5 ... 4 mm ²
Gauge Type:	A6 & 5.1 mm Dia.
Rated Short-time Withstand Current (I_{cw}):	for 1 s 1200 A
Rated Voltage (U_r):	1000 V
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Rated Cross-Section:	10 mm ²

Technical UL/CSA

Connecting Capacity Main Circuit UL/CSA:	Spring Clamp / Rigid 1x 20 ... 6 AWG Spring Clamp / With Insulated Ferrule 1x 20 ... 8 AWG Spring Clamp / Without Insulated Ferrule 1x 20 ... 8 AWG
Connecting Capacity UL/CSA:	Stranded 6 AWG
Flammability According to UL94:	V0

Environmental

Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Status:	Following EU Directive 2011/65/EC
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C

Certificates and Declarations (Document Number)

ATEX Certificate:	1SND162009A1701
BV Certificate:	1SND162013A0201

CB Certificate:	1SND162018A0201
CSA Certificate:	1SND162014A0203
cUL Certificate:	1SND162012A0203
Declaration of Conformity - CE:	1SND225151C1001
RoHS Information:	1SND230535F0201

Classifications

ETIM 4:	EC000901 - Ground terminal block
ETIM 5:	EC000901 - Ground terminal block

Container Information

Package Level 1 Width:	100 mm
Package Level 1 Length:	202 mm
Package Level 1 Height:	50 mm
Package Level 1 Gross Weight:	0.887 kg
Package Level 1 EAN:	3472597101519
Package Level 2 Units:	180 piece
Package Level 2 Width:	300 mm
Package Level 2 Length:	400 mm
Package Level 2 Height:	200 mm
Package Level 3 Units:	8640 piece
Product Packing Type:	Box
Package Level 1 Units:	20 piece



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
ZK10-PE-3P PI-Spring clamp Terminal Block - Ground - Green Yellow - 10 mm ² - 10 mm 0.394 in spacing - Flat marking area	1SNK710151R0000	ZK10-PE-3P	Buy on EAN