B.E.G.

SYSTEM WALL LIGHTS WITH MOTION DETECTOR

FOR ENERGY SAVING, SAFETY AND COMFORT


LUXOMAT® AL2-RC-plus 130




white with globe Hamburg



black





■ TECHNICAL DATA



230 V~ ±10 %



130°



max. 16 m by walking across (tangential)

IP 🗆

IP44 / Class II / C€

L 182 x W 102 x H 175 mm

-25°C to +50°C



made of high-quality and UVresistant polycarbonate

IR-RC, IR-RC-Mini

Lamps



max. 100W - conventional lamp or E27 energy-saving lamp

Channel 1 (light control)

1000 W, $\cos \varphi = 1$



15 sec. - 16 min. or pulse function




2 - 2000 Lux

■ System shades (see page 22)



(i) PRODUCT INFORMATION

- Remote controllable system light lower sections LUXOMAT® AL2-RC-plus SLS
- Freely combinable with 17 different System-Globes SG - see below!
- Tried-and-tested RC-plus motion-detector technology with 130° detection range
- 360° creep zone protection for full security, may be activated or deactivated using the LUXOMAT® IR-RC remote control.
- Wall, ceiling, inside and outside corner installation
- Time-saving single-handed plug-in base installation
- Continuous light ON and OFF possible at any time with the optional LUXOMAT® IR-RC-Mini remote control
- Connection of external lights possible
- Application examples: monitoring of an entire side of a house, entrance areas, garages, at entrance gates
- Wiring diagrams on page 79, 80!
- Remote controls on page 74, 75!



■ ACCESSORY (OPTIONAL)



. separately)

IR-RC-Mini



(to order

AL2-RC-plus-ES corner base for outside and inside corner installation



white



black



RC element



Energy and environment balance sheet see page 15

Description	Colour	Part number	
AL2-RC-plus 130 SLS	white	92381	
AL2-RC-plus 130 SLS	black	92391	
Accessory (optional)			
LUXOMAT® IR-RC	grey	92000	
LUXOMAT® IR-RC-Mini	grey	92090	
AL2-RC-plus corner base	white	92373	
AL2-RC-plus corner base	black	92414	
RC element	white	10880	