LUXOMAT® CdS-T-SM





■ TECHNICAL DATA

 (\sim) 230 V~ ±10 %

IP 🗆 IP54 / Class II / C€

L 47 x W 57 x H 65 mm

-25°C to +50°C

made of high-quality and UVresistant polycarbonate

IR-CdS-T

Energy-saving function: "Light off" with flexible settings (only with IR-CdS-T)


Channel 1 (light control)


2300 W, $\cos \varphi = 1$ 1150 W, $\cos \varphi = 0.5$

(\$ 2 - 300 Lux



- Remotely controllable LUXOMAT® CdS-T-SM photocell with integrated
- Can be remotely controlled with the LUXOMAT® IR-CdS-T - infrared remote control – more functions than with a traditional control dial
- Energy-saving period may be programmed with the integrated timer by the touch of a button
- Inputting the current light value by the touch of a button
- Application examples: ideal for entrance areas, staircases, halls where permanent light is required
- Wiring diagrams on page 81!
- ▶ Remote controls on page 76!





ACCESSORY (OPTIONAL)



separately)

Description	Colour	Part number
CdS-T-SM	white	92367
Accessory (optional)		
LUXOMAT® IR-CdS-T	grey	92368

PHOTOCELLS / CONSTANT LIGHT CONTROLS