

### LUXOMAT® PD4-DIM-KNX/EIB-GH-SM




Suitably for high-bay storages



SM


SM



#### ■ TECHNICAL DATA

- 24 VDC from KNX/EIB-BUS
- 360°
- across Ø 44.00 m
- SM = IP20 / Class II / C €
- Ø 98 x H 65 mm
- 25°C to +55°C
- Housing UV- and shock-resistant Polycarbonate
- for integration in KNX/EIB-BUS systems**

► Before programming, please note the device and software version.




#### ❗ PRODUCT INFORMATION

- Occupancy detector **LUXOMAT® PD4-DIM-KNX/EIB-GH-SM** (surface mounting version) for building services engineering, which based on KNX/EIB-BUS-network (European Installation Bus)
- **Application examples:** monitoring of warehouses, high-bay storages, wherever at a great mounting height is necessary
- **Application possibilities:**
  - With integrated bus coupler! Connection via WAGO standard bus connector
  - When using the BEG\_DIM\_HKL\_V4.0 application program, four different operating modes are available:
    - Standard mode (semi-automatic or fully automatic mode (**switching**))
    - Semi-automatic or fully automatic mode with **daylight-dependent regulation (dimming)**
    - Slave mode
    - **NEW:** Permanent dimmer (light control that is not dependent on presence)
  - Specification of three target values: Two target values are regulated (specified in Lux) and one target value is a fixed setpoint (specified in %)
  - Target values can be changed using a communication object.
  - Soft start to slowly switch on the lighting to the target value
  - **NEW:** Reflection factor for improved adjustment to the ambient conditions
  - **NEW:** HVAC channels (switch channels) can now be switched using a pushbutton
  - **Main communications objects:**
    1. 1x switch outlet or 2x light regulator outlets
    2. 2x switch channels for occupancy detection or activation of HVAC systems (HVAC= heating, ventilation, air conditioning)
    3. Issuing of the currently measured lux value

#### ■ ACCESSORY (OPTIONAL)

Wire basket



Socket IP54



SM-Socket IP65



Blinds see page 16!

Slaves PD4-DIM-KNX/EIB-GH see page 11!

Description	Colour	Part number
PD4-DIM-KNX/EIB-GH-SM	white	92454
<b>Accessory (optional)</b>		
Wire basket BSK	white	92199
Socket IP54 for PD4-SM	white	92161
SM-Socket IP65 for PD4-SM (IP20)	white	92375