


LUXOMAT® Indoor 180-DIM-KNX/EIB



■ TECHNICAL DATA

- 24 VDC from KNX/EIB-BUS
- 180°
- max. Ø 10.00 m
- IP20 / Class II / Cc
- L 87 x W 87 x D 61 mm
- 25°C to +55°C
- Housing UV- and shock-resistant Polycarbonate
- for integration in KNX/EIB-BUS systems**

▶ Before programming, please note the device and software version.



i PRODUCT INFORMATION

- Wall switch LUXOMAT® Indoor 180-DIM-KNX/EIB with semi-circular detection area for building services engineering, which based on KNX/EIB-BUS-network (European Installation Bus)
- **Application examples:** monitoring of public lavatories, corridors, archive rooms, conference rooms
- **Application possibilities:**
 - When using the BEG_DIM_HKL_V4.0 application program, four different operating modes are available:
 - Standard mode (semi-automatic or fully automatic mode (**switching**))
 - Semi-automatic or fully automatic mode with **daylight-dependent regulation (dimming)**
 - Slave mode
 - **NEW:** Permanent dimmer (light control that is not dependent on presence)
 - Specification of three target values: Two target values are regulated (specified in Lux) and one target value is a fixed setpoint (specified in %)
 - **NEW:** Reflection factor
 - **NEW:** HVAC channels (switch channels) can now be switched using a pushbutton
 - **Main communications objects:**
 1. 1x switch outlet or 2x light regulator outlets
 2. 2x switch channels for occupancy detection or activation of HVAC systems (HVAC= heating, ventilation, air conditioning)
 3. Issuing of the currently measured lux value
- **Covers sold separately!**

■ ACCESSORY (OPTIONAL)

Covering IP20

Covering IP54

SM-Socket

pure white,
RAL9010traffic white,
RAL9016cream white,
RAL1013anthracite,
RAL7021silver,
RAL9006pure white,
RAL9010pure white,
RAL9010Blinds
see page 16!

Slaves Indoor 180-DIM-KNX/EIB see page 15!

Description	Colour	Part number
Sensor insert for Indoor 180-DIM-KNX/EIB-FM	—	92436
Accessory for sensor insert		
Covering IP20	pure white, RAL9010	92630
Covering IP20	traffic white, RAL9016	92631
Covering IP20	cream white, RAL1013	92632
Covering IP20	silver, RAL9006	92633
Covering IP20	anthracite, RAL7021	92634
Covering IP54	pure white, RAL9010	92139
Accessory (optional)		
SM-Socket for Indoor	pure white, RAL9010	92141