MOTION DETECTORS FOR OUTDOOR USE

FOR ENERGY SAVING, SAFETY AND COMFORT

LUXOMAT® RC-plus next 280














- ▶ Remote controls on page 118, 119!
- Wiring diagrams on page 143 145!
- Installation note Arc extinction kit: on page 20!

TECHNICAL DATA





max. 20 m when walking across (tangential)



IP54 / Class II / (€



L121 x W71 x H85 mm



-25°C to +50°C

Housing UV- and shockresistant polycarbonate



IR-RC, IR-RC-Mini

Channel 1 (light control)


3000 W, $\cos \varphi = 1$; 1500 VA, $\cos \varphi = 0.5$



15 sec. - 16 min. or pulse for bell function



2 - 2000 Lux



(i) PRODUCT INFORMATION

■ Motion detector LUXOMAT® RC-plus next with detection area of 280°

- 360° anti-creep for a gapless monitoring, connectible and disconnectible with remote control LUXOMAT® IR-RC.
- **NEW:** energy saving by courtesy of follow up accommodation
- Additional cover clips also ensure stepless adjustment of the detection area
- Three modern sensors with three separate detection areas and three separate indications of the performance tests
- Detection of the direction of motion and improved range test mode
- Detector is compatible to the socket base of LUXOMAT® RC-plus and LUXOMAT® Vario
- The product is programmed for immediate use (time 3 min. / Lux value 20 Lux).
- Wall-, ceiling- and outside corner mountable
- Special base for corner mounting included
- Inserting of the connection cable possible from top down, from below and from
- Easy installation with plug-in socket
- Application examples: monitoring two sides of a building, warehouses

ACCESSORY (OPTIONAL)






separately)





Anti-creep





see page 20!



Arc extinction kit see page 20!

Description	Colour	Part number
RC-plus next 280	white	97003
RC-plus next 280	brown	97013
RC-plus next 280	black	97023
Accessory (optional)		
LUXOMAT® IR-RC	grey	92000
LUXOMAT® IR-RC-Mini	grey	92090
Wire basket BSK	white	92467