

LUXOMAT® LC-plus 280



white




brown



black



silver



- ▶ Remote controls on page 120, 121!
- ▶ Wiring diagrams on page 143 - 145!
- ▶ Installation note - Arc extinction kit: on page 20!

TECHNICAL DATA


- 230V~ ±10%
- 280°
- max. 16 m when walking across (tangential)
- IP44 / Class II / C €
- L 110 x W 68 x H 78 mm
- 25°C to +50°C
- Housing UV- and shock-resistant polycarbonate
- IR-LC-plus, IR-LC-Mini

Channel 1 (light control)

- 2000 W, $\cos \varphi = 1$;
1000 VA, $\cos \varphi = 0.5$
- 15 sec. - 16 min. or pulse for bell function
- 10 - 2000 Lux

PRODUCT INFORMATION

- New, electronic micro processor controlled motion detector with 360°-anti-creep for a gapless monitoring
- Spherical head adjustable
- The detection area can be altered by blinds, which are included. The blinds can be clipped-on and moved to stop unwanted detection, making it possible to achieve detection areas of less than 280°, such as 90°, 130° or 230°. Blinds included, also for 360° anti-creep cover.
- Adjustment light level and time setting by screwdriver or potentiometers at the bottom of the detector ball.
- The product is programmed for immediate use with light level 20 Lux and time setting 3 min.
- Mounting bracket for outside corners included (**supplied as standard**)
- Easy installation with plug-in socket
- **Application examples:**
monitoring two sides of a building, warehouses, parking lots



- 1 Walking towards
- 2 Walking across
- Anti-creep

ACCESSORY (OPTIONAL)

IR-LC-plus



(to order separately)

IR-LC-Mini



(to order separately)

Wire basket

Blinds
see page 20!Arc extinction kit
see page 20!

Description	Colour	Part number
LC-plus 280	white	91008
LC-plus 280	brown	91018
LC-plus 280	black	91028
LC-plus 280	silver	91048
Accessory (optional)		
LUXOMAT® IR-LC-Mini	grey	92093
LUXOMAT® IR-LC-plus	grey	92095
Wire basket BSK	white	92467