




Automatzación Eléctrica

Especialistas en Automatzación

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)



Description	Colour	Page	Part number
PD4-M-2C-SM	white	55	92140
PD4-M-2C-FC	white	55	92148
PD4-M-2C-FM	white	55	92255

■ Application description:

Automatic lighting control with motion detectors is to be implemented in a triple gymnasium. One lighting group per hall area is to be formed and switched individually.

Even with the automatic control, it should be possible to manually influence the current switching status via both a button and using a remote control.

■ Building information:

Type: gymnasium with daylight

Dimensions: L 40.00 x W 18.00 m

Room height: 8.00 to 10.00 m (in light)

■ Illumination:

One lighting group with electronic ballast per hall section

■ Products shown:

3 each LUXOMAT® PD4-Master

■ Device settings:

Switch-off delay time R1: > 5 min.

Brightness switching value: 500 Lux or individual using remote control

Switch-off delay time R2: optional

■ Connected circuit:

Master operation for all three lighting groups;

Master/Slave operation is likewise possible.

The Master unit must always be mounted at the point with the least proportion of daylight.



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Occupancy detector PD4/M-SM surface mounting	92140		Buy on EAN
Occupancy detector PD4-M-2C-FC	92148		Buy on EAN