

LUXOMAT® PD3N-SM/-FC/-FM-ZW



Bidirectional



SM

NEW!



FC



FM


■ TECHNICAL DATA

- ~ 230V ~ ±10%
- ☉ 360°
- ↔ across Ø 10.00 m
towards Ø 6.00 m
- IP □ SM = IP44; FC = IP23;
FM = IP20 / Class II / CEE
- ↗ SM Ø 106 x H 53 mm
FC Ø 83 x H 81 mm
FM Ø 106 x H 63 mm
- 🌡 +15°C to +50°C
- ☐ Housing UV- and shock-resistant polycarbonate
- 📶 IR-SMARTHOME
- 📶 **Wireless channel**
- 📶 868.42 MHz / < 10 mW
Wireless range max. 100 m
- 🕒 30 sec. - 30 min.
- ☀ 10 - 2000 Lux

- ▶ For additional information about the wireless system, please request our SMARTHOME catalogue.
- ▶ Remote controls on page 124!

❗ PRODUCT INFORMATION

- Wireless motion detector LUXOMAT® PD3N-ZW in surface-mount, ceiling-mount and flush-mount version with circular detection area, which sends a wireless signal to a wireless receiver when a movement is detected or a preset twilight value is reached.
- Settings manually on the detector or with remote control IR-SMARTHOME
- **Typical applications:** monitoring of corridors, hobby rooms, garages



- 1 Walking towards
- 2 Walking across
- 3 Smaller movements

■ ACCESSORY (OPTIONAL)

IR-SMARTHOME

Wire basket

FM Receiver module


Socket receiver module

SM Receiver module

Repeater

Blinds
see page 36!

(to order separately)



Description	Colour	Part number
PD3N-SM-ZW	white	92072
PD3N-FC-ZW	white	92071
PD3N-FM-ZW	white	92067
Accessory (optional)		
LUXOMAT® IR-SMARTHOME	grey	90162
Wire basket BSK	white	92199
A-FM-ZW	white	92805
A-ST-ZW	white	92817
A-SM-ZW	white	92807
Repeater ZW	white	92189