SWITCHING WITH 2-CHANNELS OCCUPANCY DETECTOR AS MASTER VERSION

(MOTION DETECTOR FOR INSIDE USE)

LUXOMAT® PD4-M-2C-SM/-FC/-FM






















TECHNICAL DATA

230 V~ ±10 % $(\boldsymbol{\sim})$

O 360°

IP 🗆

L.

seated Ø 6.40 m across Ø 24.00 m towards Ø 8.00 m

SM = IP54; FC/FM = IP20 /

Class II / (€

SM Ø 101 x H 76 mm FC Ø 97 x H 103 mm FM Ø 97 x H 84 mm

-25°C to +50°C

Housing UV- and shockresistant polycarbonate

3 IR-PD-2C, IR-PD-Mini

Channel 1 (Control the lighting)

2300 W, $\cos \varphi = 1$; 1150 VA, $\cos \varphi = 0.5$

15 sec. - 30 min. or impulse

10 - 2000 Lux

Channel 2 (Control devices)


dry contact type NO, 3A, 230 V, $\cos \varphi = 1$

Alarm pulse, pulse or 5 - 120 min.

- ▶ Remote controls on page 128, 126!
- Wiring diagrams on page 149!
- Application examples on page 161, 177!
- For maximum number of connectable lights, see page 38!
- Installation note Arc extinction kit: on page 102!

(i) PRODUCT INFORMATION

- Remote controllable occupancy detector for inside use LUXOMAT® PD4-M-2C as Master version for surface, false ceiling and flush mounting with circular detection area and range of 24 m
- Two switching channels, one to switch the lighting, the second to switch other loads e.g. HVAC by potential-free relay of the detector
- The connection of a unlimited number of Slaves for reasonable extension is possible!
- Many programmes adjustable with the remote control LUXOMAT® IR-PD-2C
- Typical applications: monitoring of large areas like underground garages, gyms, warehouses, loading ramps, halls



- 1 Walking towards
- 2 Walking across
- 3 Seated activity

ACCESSORY (OPTIONAL)







IR-PD-Mini



Wire basket





SM-Socket IP65



Blinds see page 102!



Arc extinction kit see page 102!



Slaves PD4-S see page 83!

Description	Colour	Part number
PD4-M-2C-SM	white	92140
PD4-M-2C-FC	white	92148
PD4-M-2C-FM	white	92255
Accessory (optional)		
LUXOMAT® IR-PD-2C	grey	92475
LUXOMAT® IR-PD-Mini	grey	92159
Wire basket BSK	white	92199
SM-Socket IP65 for PD4-SM (IP54)	white	92376