TRIO-OCCUPANCY DETECTORS FOR DALI/DSI APPLICATIONS

TO SAVE ENERGY IN BUILDINGS

LUXOMAT® PD4-M-TRIO-DALI/DSI-SM/-FC

















■ TECHNICAL DATA

230 V~ ±10 % $(\boldsymbol{\sim})$

O 360°

seated

Ø 6.40 m Ø 24.00 m across towards Ø 8.00 m

IP 🗆 $SM/FC = IP20 / Class II / (<math>\in$

SM Ø 124 x H 85 mm FC Ø 117 x H 100 mm

-25°C to +50°C

Housing UV- and shockresistant polycarbonate

IR-PD4-TRIO-DALI

Channel 1, channel 2 and dim function (light control)

DALI/DSI-Master DALI Channel 1 and 2 max. 25 EB's

 \bigcirc 1min. - 60 min.

(**\$** 10 - 2000 Lux

Channel 3 (light control)

DALI/DSI-Master DALI Channel 3 max. 10 EB's

like Channel 1 and Channel 2

▶ Remote control on page 139!


Wiring diagrams on page 154!

For maximum number of connectable lights, see page 38!

Installation note - Arc extinction kit: on page 102!

(i) PRODUCT INFORMATION

- Remote controllable group occupancy detector LUXOMAT® PD4-M-TRIO-DALI/DSI as Master version for surface and false ceiling mounting with 3 DALI interfaces and with circular detection area
- For 2 separate light groups
- Two integrated light sensors for automatic constant light control
- Control of up to 25 digital dimming electronic ballasts and control modules as a group per DALI output 1 and 2, and up to 10 for DALI output 3
- Many programmes adjustable with the remote control LUXOMAT® IR-PD4-TRIO-DALI
- Typical applications: offices, conference rooms, schools, nursery schools, hospitals



- 1 Walking towards
- 2 Walking across
- 3 Seated activity

ACCESSORY (OPTIONAL)

100 mm cut-out













Blinds see page 102!



Slaves	PD4-S
see pa	ge 83!

(to order	
separately)	

for PD4-TRIO-SM



for PD4-TRIO-FC

Description	Colour	Part number
PD4-M-TRIO-DALI/DSI-FC	white	92755
PD4-M-TRIO-DALI/DSI-SM	white	92750
Accessory (optional)		
LUXOMAT® IR-PD4-TRIO-DALI	grey	92104
Wire basket BSK for PD4-TRIO-SM	white	92467
Wire basket BSK for PD4-TRIO-FC	white	92199
SM-Socket IP44	white	92386