



**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

ITEMS	DC 12V	DC 24V
Output power	2500w continue 5000w for surge output	
Input voltage	DC 10~15 v	DC 20~30 V
Output voltage	AC 100 V,110 V,120 V,220 V,230 V,240 V	
Output voltage regulation	+/- 5 %	
Output waveform	modified sine wave	
Output frequency	50 or 60 HZ	
Battery low alarm	DC 10 +/- 0.5 V	DC 21 +/- 0.8 V
Battery low shutdown	DC 9.5 +/- 0.5 V	DC 20 +/- 0.8 V
Standby current	< 0.7A	< 0.6A
Efficiency	85~90%	
Thermal protect	60 +/- 0.5°C	
Cooling	wisdom fan start : when the temperture reach 45°C, the fan will start automatically	
Protections	soft start output short : shutdown, auto resume after solve short problem input polarity reverse : by fuse high voltage input : shutdown low voltage input : shutdown overload : shutdown overtemperture : shutdown battery low : alarm intelligent fan control trouble display : LED voltage/amps display	
Fuse	30 A * 12	15 A * 12
AC output	two AC outlet	
Size ( l * w * h )	430 * 210 * 159 mm	
Weight	8.7 kgs	





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
	A3012500W12V	A301-2500W-12V	<a href="#">Buy on EAN</a>
	A3012500W24V	A301-2500W-24V	<a href="#">Buy on EAN</a>
	A3022500W12V	A302-2500W-12V	<a href="#">Buy on EAN</a>
	A3022500W24V	A302-2500W-24V	<a href="#">Buy on EAN</a>