



**Automatización Eléctrica**

Especialistas en Automatización


At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

## Accessories, upper parts and bases V25




### Shock Guard for Multibase base

Type	Colour	Version	Pack.	Weight	Item No.
<b>MB-SG</b>	Blue	Locking system for upper parts	100 pcs	0.060 kg/100 pcs.	<b>5096 69 5</b>
PA Polyamide					/pc.




### Connecting bridge, Multibase base

Type	Version	Pack.	Weight	Item No.
<b>VB-MULTIBASE250</b>	4-pole	1 pcs	6.800 kg/100 pcs.	<b>5089 65 5</b>
/pc.				




### Empty housing for arrestors

Type	Pack.	Weight	Item No.
<b>VG LM</b>	1 pcs	139.100 kg/100 pcs.	<b>5088 87 9</b>
PA Polyamide			
/pc.			





### Upper part total spark gap between N and PE 255 V

Type	Max. continuous operating voltage V	Version	Pack.	Weight	Item No.
<b>C 25-B+C 0</b>	255	NPE	1 pcs	5.200 kg/100 pcs.	<b>5095 60 3</b>
/pc.					



### Remote signalling replacement connector for Multibase

Type	Version	Pack.	Weight	Item No.
<b>MB-FS</b>	2-pole	25 pcs	0.310 kg/100 pcs.	<b>5096 69 3</b>
/pc.				



Nominal voltage	$U_N$	V	230
SPD to EN 61643-11			Type 1+2
SPD to IEC 61643-11			class I-II
Lightning protection Zone LPZ			0-2
Lightning impulse current (10/350) (N-PE)	$I_{imp}$	kA	25
Nominal discharge current (8/20)	$I_n$	kA	30
Maximum discharge current	$I_{max}$	kA	50
Voltage protection level	$U_p$	kV	<1,2
Response time	$t_A$	ns	< 100
Follow current interrupt rating	$I_{fi}$	kA	0.1
Maximum back-up fuse		A	160
Temperature range	$\vartheta$	°C	-40 - +80
Division unit TE (17.5 mm)			1
Degree of protection of enclosure			IP20
Connection cross-section, rigid		mm <sup>2</sup>	2,5 - 35
Connection cross-section, multi-wire		mm <sup>2</sup>	2,5 - 35
Connection cross-section, flexible		mm <sup>2</sup>	2,5 - 25
<b>Item No.</b>			<b>5095 60 3</b>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
Connecting bridge for MultiBase, 250mm,	5089655	VB-MULTIBASE250	<a href="#">Buy on EAN</a>
Lightning current conductor choose N against PE,	5095603	C 25-B+C 0	<a href="#">Buy on EAN</a>
Shock Guard for MultiBase bases, Blue, Polyamide, PA	5096695	MB-SG	<a href="#">Buy on EAN</a>