


At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE

# Installation system for device installation from screed heights of 55 mm

## Multimedia connection solutions, Modul 45®




### Audio/video cinch connection, 1 module, straight outlet, as soldered connection

Type	Colour	Pack.	Weight	Item No.
		DCS	ka/100 pcs.	
MTG-12R L RW1	Pure white	1	3.200	6105 16 2

labelling panel, three cinch sockets (RCA) with soldered connection, colour coding yellow / red / white. Support plate with locking fastening, suitable for horizontal and vertical installation in the







### XLR connection, 1 module, straight outlet, 3-pin socket, as soldered connection


Туре	Colour	Pack.	Weight	Item No.
		DCS	kg/100 pcs.	
MTG-X3F L RW1	Pure white	1		6105 21 0
DO D 1 1 1				_





Multimedia support with one XLR connection socket, straight cable outlet, without labelling panel, 3-pin XLR socket with soldered connection. Support plate with locking fastening, suitable for horizontal and vertical installation in the system environment.






### XLR connection, 1 module, straight outlet, 3-pin connector, as soldered connection

туре	Coloui	Pack.	weigni	item no.
		pcs	kg/100 pcs.	
MTG-X3M L RW1	Pure white	1	3.000	6105 22 2



PC Polycarbonate

Multimedia support with one XLR connection socket, straight cable outlet, without labelling panel, 3-pin XLR connector with soldered connection. Support plate with locking fastening, suitable for horizontal and vertical installation in the system environment.




# Multimedia support for SLR plug connector, 1 module, straight

				outiet
Type	Colour	Pack.	Weight	Item No.
		pcs	kg/100 pcs.	
MTG-X O RW1	Pure white	1	0.600	6105 23 4



PC Polycarbonate

Multimedia support for a XLR plug connector, straight cable outlet, without labelling panel, without plug connector. Support plate with locking fastening, suitable for horizontal and vertical installation in the system environment.



### Antenna connection coupling, 1/2 modules, SAT


Type	Colour	Pack.	Weight	Item No.
		pcs	kg/100 pcs.	
<b>ANT-1S RW0.5</b>	Pure white	1	2.250	6117 60 6

/pc.



Single socket for antennas, BK and satellite reception systems with SAT connection.

To 1 GHz Frequency range: Through attenuation: Max. 0.055 dB



### Antenna socket, 1 module, TV / radio, single socket

Type	Colour	Pack.	Weight	Item No.
		pcs	kg/100 pcs.	
ANT-2E RW1	Pure white	10		6117 38 1

Single socket for antenna, BK and satellite reception systems with connection for TV and radio.

Frequency: 5-862 MHz Heat attenuation: 1 dB

Return channel attenuation: 14 dB

EMC protection class A





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

### To access the product, click on the green button.

Product	Code	Reference	Product link
Multimedia support audio/video 3xsocket with sold. connection, 45x45mm, Pure white, 9010, Polycarbonate, PC	6105162	MTG-12R L RW1	Buy on EAN
Multimedia support, XLR, 3-pin socket w. soldered connection, 45x45mm, Pure white, 9010, Polycarbonate, PC	6105210	MTG-X3F L RW1	Buy on EAN
Multimedia support, XLR, 3-pin connector w. sold. connection, 45x45mm, Pure white, 9010, Polycarbonate, PC	6105222	MTG-X3M L RW1	Buy on EAN
Multimedia support, XLR without connection socket, 45x45mm, Pure white, 9010, Polycarbonate, PC	6105234	MTG-X O RW1	Buy on EAN
Antenna socket single socket, Radio ¿ TV, 45x45mm, Pure white, 9010,	6117381	ANT-2E RW1	Buy on EAN
Antenna socket SAT version, 45x22,5mm, Pure white, 9010,	6117606	ANT-1S RW0.5	Buy on EAN