




Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Cable and pipe spacer clip, V4A



Type	Clamping range D	Hole size	Material	Size	Bolt	Shipping box	Pack.	Weight	Item No.
	mm	mm	mm			pcs	pcs	kg/100 pcs.	
732 6 V4A	5-6	M6	1	-	M5 x 10	-	1	-	1360 64 4
732 8 V4A	7-8	M6	1	-	M5 x 10	-	1	-	1360 64 6
732 10 V4A	9-10	M6	1	-	M5 x 12	-	1	-	1360 64 8
732 12 V4A	10.5-12	M6	1	M12	M5 x 12	-	1	-	1360 65 0
732 14 V4A	12.5-14	M6	1	PG7	M5 x 12	-	1	-	1360 65 2
732 15 V4A	13.5-15	M6	1	PG9	M5 x 12	-	1	-	1360 65 4
732 16 V4A	14.5-16	M6	1	M16	M5 x 12	-	1	-	1360 65 6
732 18 V4A	16.5-18	M6	1	PG11	M5 x 12	-	1	-	1360 65 8
732 20 V4A	18.5-20	M6	1	M20	M5 x 12	-	1	-	1360 66 0
732 22 V4A	20-22	M6	1	PG13,5	M5 x 12	-	1	-	1360 66 2
732 24 V4A	22-24	M6	1	PG16	M5 x 12	-	1	-	1360 66 4
732 26 V4A	24-26	M6	1	M25	M5 x 12	-	1	-	1360 66 6
732 28 V4A	26-28	M6	1.5	PG21	M5 x 12	-	1	-	1360 66 8
732 30 V4A	28-30	M6	1.5	PG21	M5 x 12	-	1	-	1360 67 0
732 33 V4A	31-33	M6	1.5	M32	M5 x 12	-	1	-	1360 67 2
732 35 V4A	33-35	M6	1.5	-	M5 x 12	-	1	-	1360 67 4
732 38 V4A	36-38	M6	1.5	PG29	M5 x 12	-	1	-	1360 67 6
732 40 V4A	38-40	M6	1.5	M40	M5 x 12	-	1	-	1360 67 8
732 42 V4A	40-42	M6	1.5	M40	M5 x 12	-	1	-	1360 68 0
732 45 V4A	43-45	M6	1.5	-	M5 x 12	-	1	-	1360 68 2
732 48 V4A	46-48	M6	1.5	PG36	M5 x 12	-	1	-	1360 68 4
732 50 V4A	48-50	M6	1.5	M50	M5 x 14	-	1	-	1360 68 6
732 60 V4A	58-60	M6	1.5	PG48	M5 x 14	-	1	-	1360 68 8
732 63 V4A	61-63	M6	1.5	M63	M5 x 14	-	1	-	1360 69 0

V4A Stainless steel, grade 316 Ti

/100 pc.

With thread M6.

D	A	B	x	b1	t1	t2	M
mm	mm	mm	mm	mm	mm	mm	
5-6	35	23	1	15	1	1.25	M5 x 10
7-8	34	22	1	18	1	1.25	M5 x 10
9-10	36	24	1	18	1	1.25	M5 x 12
10.5-12	38	26	1.5	18	1	1.25	M5 x 12
12.5-14	40	28	1.5	18	1	1.25	M5 x 12
13.5-15	41	29	1.5	18	1	1.25	M5 x 12
14.5-16	42	30	1.5	18	1	1.25	M5 x 12
16.5-18	44	22	1	18	1	1.25	M5 x 12
18.5-20	46	34	1.5	18	1	1.25	M5 x 12
20-22	48	36	2	18	1	1.25	M5 x 12
22-24	50	38	2	18	1	1.25	M5 x 12
24-26	52	40	2	18	1	1.25	M5 x 12
26-28	59	45	2	18	1.5	1.5	M5 x 12
28-30	61	47	2	18	1.5	1.5	M5 x 12
31-33	64	50	2	18	1.5	1.5	M5 x 12
33-35	66	52	2	18	1.5	1.5	M5 x 12
36-38	69	55	2	18	1.5	1.5	M5 x 12
38-40	71	57	2	18	1.5	1.5	M5 x 12
40-42	73	59	2	18	1.5	1.5	M5 x 12
43-45	76	62	2	18	1.5	1.5	M5 x 12
46-48	79	65	2	18	1.5	1.5	M5 x 12
48-50	81	67	2	18	1.5	1.5	M5 x 14
58-60	91	77	2	18	1.5	1.5	M5 x 14
61-63	94	80	2	18	1.5	1.5	M5 x 14





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Distance saddle with threaded connection M6, 5-6mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360644	732 6 V4A	Buy on EAN
Distance saddle with threaded connection M6, 7-8mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360646	732 8 V4A	Buy on EAN
Distance saddle with threaded connection M6, 9-10mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360648	732 10 V4A	Buy on EAN
Distance saddle with threaded connection M6, 10,5-12mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360650	732 12 V4A	Buy on EAN
Distance saddle with threaded connection M6, 12,5-14mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360652	732 14 V4A	Buy on EAN
Distance saddle with threaded connection M6, 15mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360654	732 15 V4A	Buy on EAN
Distance saddle with threaded connection M6, 14,5-16mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360656	732 16 V4A	Buy on EAN
Distance saddle with threaded connection M6, 16,5-18mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360658	732 18 V4A	Buy on EAN
Distance saddle with threaded connection M6, 18,5-20mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360660	732 20 V4A	Buy on EAN
Distance saddle with threaded connection M6, 20-22mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360662	732 22 V4A	Buy on EAN
Distance saddle with threaded connection M6, 22-24mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360664	732 24 V4A	Buy on EAN
Distance saddle with threaded connection M6, 24-26mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360666	732 26 V4A	Buy on EAN
Distance saddle with threaded connection M6, 26-28mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360668	732 28 V4A	Buy on EAN
Distance saddle with threaded connection M6, 28-30mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360670	732 30 V4A	Buy on EAN

Distance saddle with threaded connection M6, 31-33mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360672	732 33 V4A	Buy on EAN
Distance saddle with threaded connection M6, 33-35mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360674	732 35 V4A	Buy on EAN
Distance saddle with threaded connection M6, 36-38mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360676	732 38 V4A	Buy on EAN
Distance saddle with threaded connection M6, 38-40mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360678	732 40 V4A	Buy on EAN
Distance saddle with threaded connection M6, 40-42mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360680	732 42 V4A	Buy on EAN
Distance saddle with threaded connection M6, 43-45mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360682	732 45 V4A	Buy on EAN
Distance saddle with threaded connection M6, 46-48mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360684	732 48 V4A	Buy on EAN
Distance saddle with threaded connection M6, 48-50mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360686	732 50 V4A	Buy on EAN
Distance saddle with threaded connection M6, 58-60mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360688	732 60 V4A	Buy on EAN
Distance saddle with threaded connection M6, 63mm, Stainless steel, grade 316 Ti, VA, 1.4571	1360690	732 63 V4A	Buy on EAN