



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Metal pipes and accessories




4 | 4 | 5 | 7 | 1

Armoured steel pipe bend, without thread

Type	Dimension M	Dimension L	Dimension t	Dimension R	Pack.	Weight	Item No.
	mm	mm	mm	mm	pcs	kg/100 pcs.	
SB16W FT	M16	114.3	1	50.7	15	9.000	2046 60 4
SB20W FT	M20	116.55	1.2	58.45	25	13.000	2046 60 5
SB25W FT	M25	144.05	1.2	65.95	25	20.000	2046 60 6
SB32W FT	M32	172.6	1.2	62.4	20	31.000	2046 61 0
SB40W FT	M40	301.9	1.5	148.1	15	73.000	2046 61 4
SB50W FT	M50	320	1.5	173.05	5	105.000	2046 61 5
SB63W FT	M63	418.5	1.5	216.55	3	174.000	2046 61 6

St Steel **FT** Hot-dip galvanised /100 pc.

Accessory part: 90° bend with moulded sleeves, for electrical installation pipes according to EN 61386-1. With burr-free inner wall.




4 | 4 | 5 | 7 | 1

Armoured steel pipe connection sleeve, without thread

Type	Dimension M	Dimension L	Dimension D	Dimension t	Pack.	Weight	Item No.
	mm	mm	mm	mm	pcs	kg/100 pcs.	
SV16W FT	M16	50	18.6	1	25	2.000	2046 62 0
SV20W FT	M20	60	23.1	1.2	50	4.000	2046 62 1
SV25W FT	M25	60	28.1	1.2	50	5.000	2046 62 2
SV32W FT	M32	70	35.2	1.2	50	8.000	2046 62 3
SV40W FT	M40	80	43.8	1.5	25	14.000	2046 62 4
SV50W FT	M50	100	54	1.5	10	21.000	2046 62 5
SV63W FT	M63	100	67	1.5	5	28.000	2046 62 6

St Steel **FT** Hot-dip galvanised /100 pc.

Accessory part: plug-in sleeve for the connections between electrical installation pipes. With burr-free inner wall.



Stainless steel pipe, V2A




5 | 5 | 5 | 7 | 1

Type	Dimension M	Dimension L	Dimension t	Pack.	Weight	Item No.
	mm	mm	mm	m	kg/100 m	
S16 W V2A	M16	3000	1	30	36.700	2046 72 0
S20 W V2A	M20	3000	1	30	46.700	2046 72 1
S25 W V2A	M25	3000	1	30	60.000	2046 72 2
S32 W V2A	M32	3000	1.2	21	93.400	2046 72 3
S40 W V2A	M40	3000	1.2	15	116.700	2046 72 4
S50 W V2A	M50	3000	1.5	15	180.000	2046 72 5
S63 W V2A	M63	3000	1.5	9	230.000	2046 72 6

V2A Stainless steel, 1.4307 /100 m

Electrical installation pipe without threaded ends to EN 61386-1 for mechanical protection of cables. With burr-free inner wall.



Stainless steel pipe bend, V2A




5 | 5 | 5 | 7 | 1

Type	Dimension M	Dimension L	Dimension t	Dimension R	Pack.	Weight	Item No.
	mm	mm	mm	mm	pcs	kg/100 pcs.	
SB16 W V2A	M16	153	1	46	15	10.000	2046 73 0
SB20 W V2A	M20	183	1	67	25	10.000	2046 73 1
SB25 W V2A	M25	208	1	82	25	20.000	2046 73 2
SB32 W V2A	M32	258	1.2	120	20	30.000	2046 73 3
SB40 W V2A	M40	276	1.2	130	15	50.000	2046 73 4
SB50 W V2A	M50	317	1.5	150	5	90.000	2046 73 5
SB63 W V2A	M63	376	1.5	191	3	120.000	2046 73 6

V2A Stainless steel, 1.4307 /100 pc.

Accessory part: 90° bend with moulded sleeves, for electrical installation pipes according to EN 61386-1. With burr-free inner wall.



Stainless steel pipe connection sleeve, V2A




5 | 5 | 5 | 7 | 1

Type	Dimension M	Dimension L	Dimension D	Dimension t	Pack.	Weight	Item No.
	mm	mm	mm	mm	pcs	kg/100 pcs.	
SV16 W V2A	M16	45	18.2	1.6	25	2.000	2046 74 0
SV20 W V2A	M20	50	22.2	1.6	50	2.000	2046 74 1
SV25 W V2A	M25	60	27.2	1.6	50	4.000	2046 74 2
SV32 W V2A	M32	70	34.6	1.8	50	10.000	2046 74 3
SV40 W V2A	M40	80	42.6	1.8	25	10.000	2046 74 4
SV50 W V2A	M50	100	53.2	2.1	10	20.000	2046 74 5
SV63 W V2A	M63	110	66.3	2.15	5	30.000	2046 74 6

V2A Stainless steel, 1.4307 /100 pc.

Accessory part: plug-in sleeve for the connections between electrical installation pipes. With burr-free inner wall.





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
90° plug-in steel bend , Ø16mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046604	SB16W FT	Buy on EAN
90° plug-in steel bend , Ø20mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046605	SB20W FT	Buy on EAN
90° plug-in steel bend , Ø25mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046606	SB25W FT	Buy on EAN
90° plug-in steel bend , Ø32mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046610	SB32W FT	Buy on EAN
90° plug-in steel bend , Ø40mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046614	SB40W FT	Buy on EAN
90° plug-in steel bend , Ø50mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046615	SB50W FT	Buy on EAN
90° plug-in steel bend , Ø63mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046616	SB63W FT	Buy on EAN
Plug-in steel sleeve , Ø16mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046620	SV16W FT	Buy on EAN
Plug-in steel sleeve , Ø20mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046621	SV20W FT	Buy on EAN
Plug-in steel sleeve , Ø25mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046622	SV25W FT	Buy on EAN
Plug-in steel sleeve , Ø32mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046623	SV32W FT	Buy on EAN
Plug-in steel sleeve , Ø40mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046624	SV40W FT	Buy on EAN
Plug-in steel sleeve , Ø50mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046625	SV50W FT	Buy on EAN
Plug-in steel sleeve , Ø63mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	2046626	SV63W FT	Buy on EAN