



Automatización Eléctrica

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. <u>HERE</u>

Selection table

Lightcurtains and area sensors

Туре	Stacked sensors		Multibeam sensors/lightcurtains			Application specific lightcurtains	
	Ų	and the second s			Ì		
Model	E3Z	E32-M21	F3ET	F3E	E32 Area	Safety lightcurtains	Elevator lightcurtains
Key features	Mutual interference prevention	4xM3 heads com- bined in one fiber	Models with 5 to 8 mm pitch	Thin aluminium housing	Teachable sensitivity	Type 2, type 4 or application specific	Fulfills EN81-70
Max. sensing distance	60 m	1.3 m	15 m	5 m	4 m	50 m	5 m
Max. detection height	n. a.	4 m	2.1 m	1.8 m	70 mm	2.4 m	1.8 m
Page	165	213	211	212	213	See MACHINE SAFETY guide	212

Туре	Measuring lightcurtains				
			The second second		
Model	F3EM	E32 Area	ZX-GT		
Key features	cm accuracy	mm accuracy	µm accuracy		
Max. sensing distance	15 m	4 m	0.5 m		
Max. measurement height	2.1 m	70 mm	28 mm		
Page	214	213	See QUALITY CONTROL AND INSPECTION guide		







Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product Code		Reference	Product link
	127224	F39-JB1A-D	Buy on EAN