



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

## Fabric label sheet - BMK 20X 8 WH CUS - 0824231

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fabric label sheet, can be ordered: Sheet, white, labeled according to customer specifications, Mounting type: Adhesive, Lettering field: 20 mm x 8 mm

The illustration shows version BMK 38x11 in yellow

### Why buy this product

- Available in various dimensions
- Self-adhesive labels for labeling by hand or with a plotter
- Labeling service: Phoenix Contact can custom-label all BMK ... markers according to your requirements
- Secure adhesion even on curved or uneven surfaces as well as round corners



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 351096

### Technical data

#### Dimensions

Length (b)	20 mm
Width (a)	8 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

#### General

Color	white
Base element material	Polyester foil
Components	Silicone-free
Flammability rating according to UL 94	V0
Material	Polyester foil
Number of individual labels	270
Adhesive	Acrylic

# Fabric label sheet - BMK 20X 8 WH CUS - 0824231

## Technical data

### General

Printability	Plotter
Device	5144615 CMS-P1-PLOTTER
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	96 h
Wipe resistance test result	Test passed
Salt spray test specification	DIN EN 60068-2-11:2000-02
Test duration	96 h
Salt spray testing result	Test passed
Alternating condensation climate with SO2 test specification	DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Wipe resistance of test specification inscriptions	DIN EN 61010-1 (VDE 0411-1):2011-07
Result	Test passed
Marking mounting type	Adhesive

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Classifications

### eCl@ss

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27141137
eCl@ss 5.1	27141137
eCl@ss 6.0	27141137
eCl@ss 7.0	27141137
eCl@ss 8.0	27141137

### ETIM

ETIM 3.0	EC000761
ETIM 4.0	EC000761
ETIM 5.0	EC000761

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410

## Fabric label sheet - BMK 20X 8 WH CUS - 0824231

### Classifications

#### UNSPSC

UNSPSC 13.2	39121410
-------------	----------

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
Fabric label sheet, can be ordered: Sheet, white, labeled according to customer specifications, Mounting type: Adhesive, Lettering field: 20 mm x 8 mm	0824231	BMK 20X 8 WH CUS	<a href="#">Buy on EAN</a>