At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE

# Cable marker - LS-WMTB-AL (D30) BK CUS - 0831799

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Cable marker, can be ordered: Piece, aluminum color, labeled according to customer specifications, Mounting type: Assembly with cable binders, Cable diameter: >2.9 mm, Lettering field: d 30 mm

## Why buy this product

- Aluminum cable marking for assembly with cable binders
- High-quality appearance
- Suitable for large-surface marking of conductors and cables > 2.9 mm in diameter

## Key Commercial Data

| | |
|---|---|
| Packing unit | 1 STK |
| GTIN | 4 046356 930109 |

## Technical data

### Dimensions

| | |
|---|---|
| Length (b) | 30 mm |
| Width (a) | 30 mm |
| Material thickness (g) | 0.80 mm |

### General

| | |
|---|---|
| Color | aluminum color |
| Components | free from silicone, halogen, and cadmium |
| Material | Aluminum |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Printability | Direct laser marking |
| Device | 0831831 TOPMARK LASER |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result | Test passed |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN 60068-2-11:2000-02 |
| Test duration | 96 h |

# Cable marker - LS-WMTB-AL (D30) BK CUS - 0831799

## Technical data

### General

| | |
|---|---|
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result | Test passed |
| Marking mounting type | Assembly with cable binders |

### Standards and Regulations

| | |
|---|---|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 5.1 | 27400401 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 8.0 | 27400401 |

### ETIM

| | |
|---|---|
| ETIM 4.0 | EC001530 |
| ETIM 5.0 | EC001530 |

Phoenix Contact 2016 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

| Product | Code | Reference | Product link |
|---|---|---|---|
| Cable marker, can be ordered: Piece, aluminum, labeled according to customer specifications, Mounting type: Assembly with cable binders, Cable diameter: >2.9 mm, Lettering field: d 30 mm | 0831799 | LS-WMTB-AL (D30) BK CUS | Buy on EAN |