



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE



# Crimping pliers - CRIMPFOX 6H CUS - 1212768

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Crimping pliers, laser marked according to customer specifications, for ferrules according to DIN 46228, 0.14 - 6 mm², unlockable pressure lock, lateral entry

The figure shows CRIMPFOX 10S CUS

#### Why buy this product

- These compact crimping pliers have been designed to reduce effort when working
- The way in which the handles and the die are arranged means that the ferrules can be fitted however the tool is held





## **Key Commercial Data**

Packing unit	1 STK		
GTIN	4 046356 942959		

#### Technical data

#### **Dimensions**

Length (b)	175 mm
General	

Compression	HEX crimp
Type of contact	Ferrules

## Classifications

#### eCl@ss

eCl@ss 5.1	21040301
eCl@ss 6.0	27371301
eCl@ss 8.0	21049090



## Crimping pliers - CRIMPFOX 6H CUS - 1212768

## Classifications

## **ETIM**

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Crimping pliers, laser marked according to customer specifications, for ferrules according to DIN 46228, 0.14 - 6 mm², unlockable pressure lock, lateral entry	1212768	CRIMPFOX 6H CUS	Buy on EAN