



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

FO patch cable - FOC-ST:A-LC:A-GZ01/2 - 1400701

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled FO cable, zip cord cable, multi-mode fiberglass 50/125 µm, OM2, plug: LC/B-FOC (ST), degree of protection: IP20, for installation in cable ducts or control cabinets, length: 2 m

Why buy this product

- Multi-mode patch cable for indoor installation
- Ideal for use in distributor systems and for connecting termination devices
- UL approval type OFNR (riser) for USA and Canada
- 2.8 mm single elements made from halogen-free and flame-retardant material

Key Commercial Data

| | |
|--------------|---------------------|
| Packing unit | 1 STK |
| GTIN | 4 046356 735032 |

Technical data

Mechanical characteristics

| | |
|---------------------|---------------|
| Number of positions | 2 |
| Fiber | 50/125 µm OM2 |
| Type of cable | Zip cord |
| Length of cable | 2 m |
| Color | orange |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -10 °C ... 60 °C |
| Ambient temperature (assembly) | -5 °C ... 50 °C |
| Ambient temperature (storage/transport) | -10 °C ... 60 °C |

Material data

| | |
|--|-------------------|
| Flammability rating according to UL 94 | V0 |
| External sheath, color | orange |
| Ferrule material | Zirconia ceramics |

Electrical characteristics

| | |
|--------------------|-----|
| Transmission speed | OM2 |
|--------------------|-----|

FO patch cable - FOC-ST:A-LC:A-GZ01/2 - 1400701

Technical data

Standards and Regulations

| | |
|--|------------------------------|
| Halogen-free | complying with IEC 60754-1/2 |
| Flammability rating according to UL 94 | V0 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27061803 |
| eCl@ss 6.0 | 27260705 |
| eCl@ss 7.0 | 27440309 |
| eCl@ss 8.0 | 27061003 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC000034 |
| ETIM 5.0 | EC001263 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 31261501 |

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|---|---------|----------------------|----------------------------|
| Assembled FO cable, zip cord cable, multi-mode fiberglass 50/125 μm , OM2, plug: LC/B-FOC (ST), degree of protection: IP20, for installation in cable ducts or control cabinets, length: 2 m | 1400701 | FOC-ST:A-LC:A-GZ01/2 | Buy on EAN |