



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

FO connectors - FOC-C-LCDU-GOF-SM-PC - 1411053

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



LC duplex connector, with long bend protection, for single mode 9/125 µm, PC polishing, blue

Product Description

LC duplex connector, for wires 2.0 mm to 3.0 mm in diameter, single mode 9/125 µm, PC polishing.
The reusable connector is particularly suitable for quick and easy field connection, as there is no need for bonding and polishing.

Why buy this product

- suitable for quick and easy field assembly or repair
- No bonding or polishing
- Reusable connectors
- A real alternative to splicing
- Optimum attenuation values with easy assembly
- Long-term durability, thanks to the latest index matching gel
- the 8° fiber transition ensures optimum return loss (RL)
- meets IEC 61754-20 (LC) and FprEN 50377-17-1 (connectors for field assembly)
- Cleave technology
- Reusable connectors

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 922425

Technical data

Mechanical characteristics

Connection profile	LC duplex plug
Locking type	Clip locking
Fiber type	Quartz fiber
Fiber	9/125 µm
Ferrule diameter	1.25 mm
Insertion/withdrawal cycles	≥ 500 (according to IEC 61300-2-2)
Connection method	Mechanical splice
Type of contact	Index matching gel with extended temperature range

FO connectors - FOC-C-LCDU-GOF-SM-PC - 1411053

Technical data

Mechanical characteristics

Max. cable diameter	2 mm ... 3 mm
Cable exit	straight
Type of cable	For all common cable types
Cable structure	Semi-loose compact wires (STB)
Color	blue

Ambient conditions

Ambient temperature (operation)	-10 °C ... 70 °C (IEC 61300-2)
Degree of protection	IP20

Material data

Flammability rating according to UL 94	V0
Ferrule material	Zirconia ceramics

Line characteristics

Type of cable	For all common cable types
Cable type	Fiberglass
Cable structure	Semi-loose compact wires (STB)
Number of fibers	1
Fiber type	Single-mode fiberglass
Fiber	GOF
Attenuation	≤ 0.5 dB ((95%) according to IEC 61300-3-34)
	≤ 0.2 dB ((typical value) according to IEC 61300-3-34)
Tensile strength short-term/long-term	70N (120s.) bei Aderdurchmesser >2 mm
cable layer type	Indoors

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27260705
eCl@ss 8.0	19170122

ETIM

ETIM 5.0	EC001122
----------	----------

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
LC duplex connector, with long bend protection, for single mode 9/125 μm , PC polishing, blue	1411053	FOC-C-LCDU-GOF-SM-PC	Buy on EAN